

# Sefram

## SEFRAM9891 Refrigerant Leak Detector

### ■ Features :

Air Sucking System for faster response and higher sensitivity.  
Refrigerant leakage detector is the perfect tool for maintaining the air-condition or a cooling system with compressor and refrigerant.

This unit used newly developed semiconductor sensor which is extremely sensitive to variety of general used refrigerant.  
Microprocessor control with advanced digital signal processing.

### ■ Specifications :

- Heated semiconductor gas sensor
- 3 level sensitivity
- 7 LED Tri-colored leak level indicator
- Variable intensity audible alarm
- Ambient concentration reset
- 15.5" (40cm) flexible probe
- Detection of R-22, R-32, R-290, R-131a, R-404A, R-410A, R-407C, R-502, R-600A, R-1234yf... Refrigerants Gas
- Sensibility : 3g/year
- Low battery indication
- Battery life : approximately 12 hours normal use (alkaline battery)
- Reference leak source included
- Hard carrying case included
- Warm-up time: 45 seconds
- Operating temperature: 0 to 40 °C (32 to 104°F)
- Dimensions : L.22,1 x W.7,4 x H.4,7 cm
- Weight : 421g (with batteries)
- Power Source : 4 AA Size alkaline batteries



For assistance and ordering

# Sefram

32, rue Edouard Martel - BP55- 42009 - St Etienne - cedex 2  
Tél. +33 (0) 4.77.59.01.01 / Fax. +33 (0) 4.77.57.23.23  
Web : [www.sefram.com](http://www.sefram.com) - e-mail : [sales@sefram.com](mailto:sales@sefram.com)



Follow us on :



FT SEFRAM9891 A00 - Specifications can be updated without notice

Visit our website: [www.sefram.com](http://www.sefram.com)