

Specifications	
Recording interval	Customizable from 1 minute to 2 hours
Storage	More than 1 million measurements
Buzzer	Yes
Units	°C or °F
Backlighting Display Hold function Min-Max	Yes
Automatic power-off	Yes (in portable mode only)
General specifications	
Product operating range	Temperature: -10 °C to +60 ° C – Humidity: 5 to 95 %RH
Dimensions / weight	125 x 65.5 x 32 mm / 190 g with batteries
Protection	IP40
Compliance	IEC 61010-1 for 50 V in Category II – IEC 61326-1 – Compliance with French decree no. 2012-14
Power supply	- Alkaline batteries: 2 x 1.5 V AA / LR6 or rechargeable battery - Connection to mains possible with mains / micro USB adapter supplied as standard
Interfaces	2 communication modes possible: - Bluetooth wireless communication - USB link; the product is then recognized as a USB key for easy file transfer
Mounting	C.A 1510 casing equipped with a magnet, a wall-suspension system and a slot for hanging the product. A wall support for use with a padlock (padlock not supplied) is available as an accessory, as is a desktop stand (supplied as standard with the C.A 1510W).
<b>Functions of the AQR (Air Quality Report) software supplied as standard</b>	Graphic representation or as table of values – Data export – Real-time mode Calculation of the confinement index with selection of presence periods – Report generation