

Winding Resistance Measurement

- Test currents: 5 mA – 25 A DC
- Output voltage: up to 55 V DC
- Measurement range: 0,1 $\mu\Omega$ – 10 k Ω
- Typical accuracy:
 $\pm(0,1\% \text{ rdg} + 0,1\% \text{ F.S.})$ for 0,1 $\mu\Omega$ -1,999 k Ω range
 $\pm(0,2\% \text{ rdg} + 0,1\% \text{ F.S.})$ for 2 k Ω - 10 k Ω range

Resolution

- 0,1 $\mu\Omega$ – 999,9 $\mu\Omega$: 0,1 $\mu\Omega$
- 1,000 m Ω – 9,999 m Ω : 1 $\mu\Omega$
- 10,00 m Ω – 99,99 m Ω : 10 $\mu\Omega$
- 100,0 m Ω – 999,9 m Ω : 0,1 m Ω
- 1,000 Ω – 9,999 Ω : 1 m Ω
- 10,00 Ω - 99,99 Ω : 10 m Ω
- 100,0 Ω – 999,9 Ω : 0,1 Ω
- 1,000 k Ω – 9,999 k Ω : 1 Ω

Data Storage

- 1 000 internal memory positions
- USB flash drive feature enables storage of a huge number of measurements

Printer (optional)

- Thermal printer
- Graphic and numeric printout
- Paper width 80 mm

OLTC Dynamic Resistance Measurement

- Sampling rate: 0,1 ms
- Automatic open circuit detection and warning
- Transition current ripple measurement
- Transition time measurement using DV-Win software
- Timing measurement of different transition changes using DV-Win graph analysis tool

AC Current Measurement Channel

- Resolution: 0,1 ms
- Amplitude resolution: 16 bit

Current Clamp Meter Specifications

- Measuring range: 30 / 300 A
- Nominal current: 300 A_{RMS} or 450 A DC_{PK}
- Frequency range: DC to 20 kHz (-3 dB)

Computer Interface

- USB
- Optional: RS232

Warranty

- Three years

Environmental Conditions

- Operating temperature:
-10 °C - + 55 °C / 14 F - +131 F
- Storage & transportation:
-40 °C - + 70°C / - 40 F - +158 F
- Humidity 5 % - 95 % relative humidity, non condensing

Dimensions and Weights

- Thermal printer and Tap changer control unit not included:
 - Dimensions (W x H x D)
405 mm x 170 mm x 335 mm
16 in x 6.7 in x 13.2 in
 - Weight
9,5 kg / 20.9 lbs
- Thermal printer and / or Tap changer control unit included:
 - Dimensions (W x H x D)
480 mm x 197 mm x 395 mm
18.9 in x 7.75 in x 15.6 in
 - Weight
10,0 kg / 22.0 lbs