

Power supply	230V ac \pm 10%, 50Hz \pm 5% or 60Hz \pm 5% 115V ac \pm 10%, 50Hz \pm 5% or 60Hz \pm 5% 350 VA max
Test signal	Voltage: 115V rms Current: < 2A rms
Measurement ranges	Turn ratio: 0.9:3000, 7 scales Resolution: 4 ½ digits Accuracy: \pm 0.3% reading \pm 2 digits Current: 3.1:2000 mA rms, 6 scales Resolution: 3 digits Accuracy: \pm 1% reading \pm 2 digits Phase angle: -180° +180° Resolution: 3 digits Accuracy: \pm 0.15°
Measurement time	Single-phase: 20 to 35" depending on mode Three-phase: 60 to 90" depending on mode
Measurement modes	High to Low ratio High to Tertiary ratio
Environmental conditions	Temperature: 5° - 35° C / 40° - 95° F Humidity: 10 - 80% non-condensating
Storage	Temperature: 5° - 75°C / 40° - 165° F Humidity: 10 - 80% non-condensating
Physical dimensions	Depth: 40 cm / 16" - Width: 45 cm / 18"- Height: 13.5 cm / 5" Weight: 13 Kg. / 28 lb.
Test leads	Length: 2 x 8 m / 2 x 26 ft. Weight: 2 x 6 Kg. / 2 x 13 lb.