

# C.A 1110 Logger Luxmeter



## Measure lighting at any time

Spectral error compensation on LED or FLUO sources

MAP mode

Min, Max, Average and Hold functions

Spot or continuous recording up to 1 million points



Data Logger Transfer  
Automatic report generation



*Measure up*



## C.A 1110 Logger Luxmeter

<b>Measurement ranges</b>	0.1 lx to 200,000 lx (lux)	0.01 fc to 18,580 fc
<b>Resolution</b>	0.1 lx (0.1 lx to 999.9 lx) 1 lx (1 000 lx to 9,999 lx) 10 lx (10,000 lx to 99.99 klx) 100 lx beyond	0.01 fc (0.01 fc to 99.99 fc) 0.1 fc (100.0 fc to 999.9 fc) 1 fc (1,000 to 9.999 fc) 10 fc beyond

### METROLOGICAL SPECIFICATIONS

	Class C luxmeter as per the NF C 42-710 standard	Mode with compensation
<b>Intrinsic uncertainty for measurement in lux</b>	± 3% of reading on incandescent sources (by default) ± 6% of reading on LEDs (3,000 K to 6,000 K) ± 9% of reading on fluorescent sources	LED mode: ± 4% of reading (at 4,000 K) Fluo mode: ± 4% of reading (type F11, 4,000 K)

### FUNCTIONS

<b>Recording</b>	<b>Manual start/stop on the product</b> Short press for MEM: spot recording / Long press for REC: recording at the rate of the current mode <b>Programmed recording</b> Start date, recording interval (from 1 minute to 2 hours) and end date are defined using the PC software
<b>Data storage</b>	More than 1 million points
<b>Min-Avg-Max-Hold</b>	Yes
<b>MAP mode</b>	The MAP function can be used to map the lighting on a surface or in a room. In this way, the lighting measurements are saved in the same file.
<b>Units</b>	lx or fc
<b>Backlighting</b>	Yes
<b>Automatic power-off</b>	Yes (configurable)

### POWER SUPPLY

<b>Type</b>	3 x 1.5 V AA / LR6 alkaline batteries Connection to the mains possible with the mains / micro-USB adapter offered as an accessory
<b>Battery life</b>	500 hrs (portable mode) / 3 years of recording (15-minute measurement interval)

### PHYSICAL SPECIFICATIONS

<b>Interfaces</b>	2 possible communication modes: Bluetooth wireless link and USB
<b>Mounting</b>	Casing equipped with a magnet, a wall-mount system and a slot for suspending the product Compatible with the Multifix accessory
<b>Dimensions / weight</b>	Casing: 150 x 72 x 32 mm / Sensor: 67 x 64 x 35 mm / 345 g with batteries
<b>Ingress protection</b>	IP50
<b>Product operating range</b>	Temperature: -10 to +60 ° C / Humidity: 0 to 90 %RH
<b>Compliance</b>	IEC61010-1 / IEC 61326-1 / Class C luxmeter as per the French NF C 42-710 standard based on the CIE guidelines

### GENERAL SPECIFICATIONS

<b>Data Logger Transfer Windows PC software functions</b>	Display as a graph or a table of values / Data export in graph or Excel table form Real-time mode / Automatic report generation in Word format / Data format compatible with the Dataview software offered as an accessory
<b>Warranty</b>	2 years

### Accessories / Replacement Parts

Shockproof sheath + Multifix .....	P01654252
Multifix .....	P01102100Z
Mains adapter .....	P01651023
Bag .....	P01298075
Metal case .....	P01298071
Dataview software .....	P01102095
BLE Bluetooth modem / USB for PC .....	P01654253
4xAA/LR6 NiMH Batteries + Battery charger .....	HX0053

### Standard state at delivery:

**Bag, 3x1.5V AA alkaline batteries, USB cable, test report and quick start-up guide** (complete manual and Data Logger Transfer software available from the Chauvin Arnoux website)



**TO ORDER**

**C.A 1110 Logger Luxmeter**  
..... P01654110