

**30XR-A**

<b>Display</b>	LCD, 1999 digiti	
<b>Tensiune CA</b>	0,1 mV...600 V	$\pm(1,5\% \text{ rdg} + 4 \text{ digiti}) @ 45 \text{ Hz} \dots 500 \text{ Hz}$
<b>Tensiune CC</b>	0,1 mV...600V	$\pm(1\% \text{ rdg} + 1 \text{ digit}) @ 10 \text{ M}\Omega$
<b>Curent CA</b>	0,1 $\mu\text{A} \dots 10\text{A}$	$\pm(2\% \text{ rdg} + 4 \text{ digiti}) @ 45 \text{ Hz} \dots 500 \text{ Hz}$
<b>Curent CC</b>	0,1 $\mu\text{A} \dots 10\text{A}$	$\pm(2,0\% \text{ rdg} + 3 \text{ digiti})$
<b>Rezistenta</b>	0,1 $\Omega \dots 20 \text{ M}\Omega$	$\pm(1\% \text{ rdg} + 4 \text{ digiti})$
<b>Continuitate</b>	R < 75 $\Omega$	
<b>Clasa</b>	CAT III/300V, CAT II/600V	
<b>Certificare</b>	EN 61010, IEC 61010	
<b>Baterie</b>	1 x 9V	
<b>Dimensiuni</b>	196 x 92 x 60 mm.	
<b>Greutate</b>	~ 426 g. (incl. baterie)	