

37XR-A

Display	LCD, 9999 digiti	
Tensiune CA	0,1 mV...750 V	$\pm(1,2\% \text{ rdg} + 10 \text{ digiti}) @ 45 \text{ Hz} \dots 2 \text{ kHz}$
Tensiune CC	0,1 mV...1000V	$\pm(0,1\% \text{ rdg} + 5 \text{ digiti}) @ 10 \text{ M}\Omega$
Curent CA	0,01 μA ...10A	$\pm(1,5\% \text{ rdg} + 10 \text{ digiti}) @ 45 \text{ Hz} \dots 1 \text{ kHz}$
Curent CC	0,01 μA ...10A	$\pm(0,5\% \text{ rdg} + 10 \text{ digiti})$
Rezistentă	0,1 Ω ...40 M Ω	$\pm(0,5\% \text{ rdg} + 8 \text{ digiti})$
Continuitate	R < 40 Ω	
Ciclu de lucru	0..90%	$\pm(2,0\% \text{ rdg} + 20 \text{ digiti})$
Frecvență	3,00 Hz...10 MHz	$\pm(0,1\% \text{ rdg} + 5 \text{ digiti})$
Capacitanță	0,01 nF...400,0 μF	$\pm(3,0\% \text{ rdg} + 10 \text{ digiti})$
Inductanță	1 μH ...40,00 H	$\pm(5,0\% \text{ rdg} + 30 \text{ digiti})$
Atenuare	-13 dBm...+50 dBm	$\pm(0,7\% \text{ dB} + 8 \text{ digiti})$
Clasa	CAT III/600V, CAT II/1000V	
Certificare	EN 61010, IEC 61010	
Baterie	1 x 9V	
Dimensiuni	196 x 92 x 60 mm.	
Greutate	~ 482 g. (incl. baterie)	