

		AM-500-EUR
Tensiune AC	Domeniu	2,000 / 20,00 / 200,0 / 600V
	Precizie	± (1.0 % rdg. + 3 diti) @ 45 Hz...400 Hz
Tensiune CC	Domeniu	200mV, 2,000/20,00/200,0/600V
	Precizie	± (0.8 % rdg. + 1 digit) @ 2...200V
Curent AC	Domeniu	200,0 / 2000 µA 20,00 / 200,0 mA 2,000 / 10,00 A
	Precizie	± (1.2 % rdg. + 2 diti) @ 200,0 µA...200,0 mA
Curent CC	Domeniu	200,0 / 2000 µA 20,00 / 200,0 mA 2,000 / 10,00 A
	Precizie	± (1.0 % rdg + 2 diti) @ 200,0 µA...200,0 mA
Rezistenta	Domeniu	200,0 Ohms 2,000 / 20,00 / 200,0 kOhms 2,000 / 20,00 MOhms
	Precizie	± (1,0 % rdg. + 2 diti) @ 2 kOhms ... 200 kOhms
Continuitate		beeper la R ≤ 10 Ω, off >150 Ω
Test dioda		Da
Temperatura de operare		0°C...+40°C
Clasa		CAT III / 600V
Alimentare		2 x 1,5 V
Dimensiuni		150 x 83 x 40 mm
Greutate		290 g (incl. baterii)