

# Identification Systems

## Report Generating Accessories

3-349-475-03  
17/6.16

### Z502F, Z720A and Z751A Barcode Scanners

- Scanning distances of up to 35 cm
- Green Spot technology

### Z721D Barcode Printer

- High speed device
- Can be integrated into networks

### Z751G RFID Read / Write

- Combined read and write system for 13.56 MHz transponders
- RS 232 interface

### Z751E RFID Read / Write

- Combined read and write system for 13.56 MHz transponders
- USB-HID interface

### Thermal Printer Z721S

- Thermal line dot printer for text
- USB interface



## Application

Barcode and RFID identification systems are used to mark and identify tools and equipment.

The scanning devices are exclusively matched to the interfaces included with SECUTEST, PROFITEST, MINITEST, SECUSTAR and SECULIFE test instruments. They forward the scanned code to the respective test device in order to be able to allocate measured values and test results to the device under test in an unequivocal fashion.

ID numbers can be written to RFID tags with the SCANBASE RFID devices (Z751G and E). ID numbers can be printed onto barcode labels with the barcode printer and a PC.

## Features

### Z720A, Z751A and Z502F Barcode Scanners

These devices are based upon the concept of an instinctive scanning distance and provide best possible reading performance at distances of up to 35 cm. Green Spot technology projects "good-read" indication directly onto the code. The Z720A / Z502F is equipped with an RS 232 port, and the Z751A with a USB port.

### Z721D Barcode Printer

High performance, fast, PC compatible labeling system. Prints especially high quality, durable labels. The device is particularly well suited for printing resilient barcode labels.

### Z751G SCANBASE RFID: RFID Reader / Writer \*

Compact reading and writing device with RS 232 port for programming and reading 13.56 MHz transponders in accordance with ISO15693.

### Z751E SCANBASE RFID: RFID Reader / Writer \*

Compact reading and writing device with USB port for programming and reading 13.56 MHz transponders in accordance with ISO15693.

\* configured for German keyboard layout

## Applicable Regulations and Standards

DIN EN 61326  
VDE 0843, part 20

Electrical equipment for control technology and laboratory use – EMC requirements

# Identification Systems

## Report Generating Accessories


### Device Overview


					
Designation	Barcode Scanner			RFID Read/Write	
Type	Z720A	Z502F	Z751A	SCANBASE RFID	SCANBASE RFID
Feature Article no.	Z720A	Z502F	Z751A	Z751E <sup>2) 4)</sup>	Z751G <sup>2) 3) 4)</sup>
Connection interfaces	RS232	RS232	USB	USB-HID	RS232
Connection cable (2 m)	stright	coiled	stright	stright	stright
Frequency	—			13.56 MHz	
Readable codes (selection), RFID tags	Code 39, code 128, EAN 13 (12 digits) <sup>1)</sup>			ISO15693, Z751R, Z751S, Z751T	
Scanning distance	Max. 350 mm <i>new!</i>			Approx. 30 mm	Approx. 30 mm
Power supply	Via interface			Via interface	
Operating temperature	0 °C ... 50 °C			-10 °C ... 55 °C	
Dimensions	163 x 91 x 41 mm <i>new!</i>			240 x 120 x 35 mm	
Usable for following devices and product ranges	SECUTEST PSI <sup>5)</sup> , SI+ <sup>5)</sup> , SECUSTORE, PROFITEST 204, PROFITEST M ..., MINITEST MASTER, MINITEST 3P MASTER, SECUTEST S2N+(10), SECUTEST SIII+, SECUTEST 3PL, SECULIFE ST		SECUSTAR FM, SECULIFE SB, SECUTEST BASE(10)/PRO	SECUSTAR FM, SECULIFE SB, SECUTEST BASE(10)/PRO (SECUTEST BASE with database extension and PRO enable the user to populate the RFID tags directly from the test instrument with the help of the programmer.)	MINITEST MASTER, MINITEST 3P MASTER, SECUTEST S2N+(10), SECUTEST SIII+, SECUTEST 3PL, SECULIFE ST, PROFITEST 204, PROFITEST M ..., SECUSTORE

Data and pictures marked with *new!* only apply to devices which start with serial numbers G15(E)... and are manufactured and supplied as of August 2015.

<sup>1)</sup> For more decoding options refer to the table on the following page  
<sup>2)</sup> In order to program the RFID tags, the respective RFID scanner/programmer must be connected to the PC by using the software which is available on the attached CD ROM.

<sup>3)</sup> Please note: Z751GA requires a special RS232 cable and power supply unit which are both available from our Customer Service Center. The contact address is given on the last page.  
<sup>4)</sup> configured for German keyboard layout  
<sup>5)</sup> see footnote (\*) on page 4

	
Designation	Barcode Printer
Type	Z721D
Feature Article no.	Z721D
Connection interfaces	To the PC: USB, serial
Text entry	Via PC keyboard
Fonts	All of the computer's true type fonts
Font sizes	1.2 to 27 mm
Label tape	TZ, AL, HG
Label tape width	6, 9, 12, 18, 24, 36 mm (TZ/HG), 24 mm (AL)
Print resolution	360 dpi
Printing speed	Up to 80 mm per second
Power supply	Power pack
Weight	1.6 kg
Dimensions	116 x 192 x 140 mm






	
Designation	Thermal Printer for SECUTEST BASE(10)/PRO
Type	Z721S
Feature Article no.	Z721S
Connection interfaces	To the PC: USB, IrDA, serial
Method	Thermal line dot printing
Fonts	Extended graphics character set
Paper width	112 mm
Printing width	104 mm
Print resolution	8 Pixel/mm
Printing speed	90 mm/s
Power supply	Power supply adapter with mains cable
Weight	0,5 kg
Dimensions	15 x 14 x 6 cm (W x D x H)

# Identification Systems Report Generating Accessories

*new!* More Decoding Options for Z720A, Z502F and Z751A

Code types	Codes in detail
<b>1D codes / linear codes (barcodes)</b>	Automatic recognition of all standard linear codes and linear GS1 DataBar™ codes
<b>2D codes</b>	Aztec Code; Aztec Mesas; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code
<b>Post codes</b>	Australian Post; British Post; Canadian Post; China Post; Japanese Post; KIX Post; Korea Post; Planet Code; Postnet; Royal Mail Code (RM4SCC)
<b>Staple codes</b>	EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites

## Accessories Overview

				No photo		
<b>Designation</b>	<b>RFID Tag</b>				<b>Label Tape Cartridge</b>	
Type	Z751R	Z751S	Z751T	ZxxxX	Z722D	Z722E
Feature	Z751R	Z751S	Z751T	ZxxxX	Z722D	Z722E
Article no.	Z751R	Z751S	Z751T	ZxxxX	Z722D	Z722E
Usable for following devices	Z751E, Z751G				Z721D	
Frequency	13.56 MHz			125 kHz	—	
Chip	ICODE SLI with 1 kBit data memory				—	
Writing cycles	100,000				—	
Reading cycles	Unlimited				—	
Material	ABS				—	
Temperature range	-20 ° to +60 °C				—	
Standard	ISO 15693			HITAG1, 2, S, Q5, Titan, Atmel5577, EM-4XXX	—	
Type	Dia. approx. 22 mm, self-adhesive (the photos show the front, as well as the adhesive back)	Dia. approx. 30 mm thickness 2 – 3 mm with 3 – 4 mm hole	Pigeon ring, dia. approx. 7.5 mm	Upon request	Cartridge	
Quantity per package	500 pieces		250 pieces	1000 pieces	1 set of labels includes the following label tape cartridges: 3 x 24 mm wide, 1 x 18 mm wide, 1 x 9 mm wide, length: 8 m each	1 set of labels includes the following label tape cartridges: 5 x 18 mm wide, length: 8 m each

# Identification Systems

## Report Generating Accessories

### Order Information

Description	Type	Article Number
<b>Barcode Scanners</b>		
Barcode scanner for RS 232 connection (laser sensor), variable barcode length, enhanced reading accuracy	Z720A *	Z720A
Barcode scanner for RS 232 connection (laser sensor), variable barcode length, enhanced reading accuracy, with coil-cable	Z502F *	Z502F
Barcode scanner for USB connection	Z751A *	Z751A
<b>Barcode Printer</b>		
Barcode and label printer including software, for USB and RS232 connection to the PC	Z721D	Z721D
<b>Accessories</b>		
Label set for Z721D barcode and label printer (quantity x width: 3 x 24, 1 x 18, 1 x 9 mm, length: 8 m each)	Z722D	Z722D
Label set for Z721D barcode and label printer (qty. x width: 5 x 18 mm, 8 m long each)	Z722E	Z722E
<b>RFID Readers / Scanners</b>		
RFID read/write for USB connection (frequency: 13.56 MHz)	SCANBASE RFID	Z751E
RFID read/write for RS 232 connection (13.56 MHz)	SCANBASE RFID	Z751G
<b>Accessories</b>		
RFID tags per ISO 15693, dia. approx. 22 mm, self-adhesive, 500 pcs.	Z751R	Z751R
RFID tags per ISO 15693, dia. approx. 30 mm, thickness 2 – 3 mm with 3 – 4 mm hole 500 pcs.	Z751S	Z751S
RFID tags per ISO 15693, pigeon ring, dia. approx. 7.5 mm, 250 pcs.	Z751T	Z751T
RFID tag (125 kHz), shape as requested, 1000 pcs.	ZxxxX	ZxxxX
<b>Thermal printer for SECUTEST BASE(10)/PRO</b>		
Thermal printer for printing out test reports; inkl. manual on CD, Lithium-Batterie, power supply adapter, mains cable, 1 roll of Thermopaper	Z721S	Z721S
<b>Accessories</b>		
Thermo paper for Z721S; 10 roll of thermo paper, Ø 12/50mm, 30 m x 112 mm	Z722S <sup>D</sup>	Z722S

\* Connection with a SECUTEST (P)SI+ module up to and including year of manufacture 2015 (up to serial number AZ..) requires a retrofit of the SECUTEST (P)SI+ module. Please contact our service for this purpose at: [www.gmci-service.com](http://www.gmci-service.com)

<sup>D</sup> Data sheet available

For additional information regarding accessories please refer to:

- The data sheet for the respective device or our Measuring Instruments and Testers catalogue.
- [www.gossenmetrawatt.com](http://www.gossenmetrawatt.com)

Edited in Germany • Subject to change without notice • PDF version available on the Internet



GMC-I Messtechnik GmbH  
Südwestpark 15  
90449 Nürnberg • Germany

Phone +49 911 8602-111  
Fax +49 911 8602-777  
E-Mail [info@gossenmetrawatt.com](mailto:info@gossenmetrawatt.com)  
[www.gossenmetrawatt.com](http://www.gossenmetrawatt.com)