

Device:

Construction	17,8 x 12,7 x 10,2 cm/ABS Plastik
Weight	< 3 Lbs (< 1,36 kg)
Face Plate	Lexan/Back printed
Operating Range	15 to 40 °C
Storage Range	-20 to 65 °C

General	
Display	LCD Graphical 128 x 64 pixel
Backlight	Yes
Lead Test Terminals	No
RS232	Yes
Power	6 x 1,5 V AA
Battery Eliminator	Yes

Functions:

ECG-NSR	Yes
Leads	10
Rates	4
Amplitudes	1
QRS Interval	Adult, Neonatal, Hypertensive, Hypotensive
ST Segment Elevation	No
ECG-Performance	Yes
Sine Waves	3
Square Waves	2
Triangle Waves	1
Pulse Waves	-
Respiration	Yes
Rate	4
Baseline	1
Delta Impedance	1
NIPB	Yes
Rates	80,94 BPM
Pressure Output	± 500 mm Hg
Special Modes	Yes
SpO2 Simulation	With Seculife OX
Lead Test	Yes
Manometer	Yes

Pacemaker	Yes
Arrhythmias	6
Blood Pressure	1
Temperature	YSI 400/700 0, 24, 30, 37, 40 °C (± 0.1 °C Accuracy)