

Earth continuity (200 mA in to 2.00 Ω)

Range	Resolution	Accuracy
0.00 Ω ÷ 19.99 Ω	0.01 Ω	± (5 % of reading + 3 digits)
20.0 Ω ÷ 199.9 Ω	0.1 Ω	
200 Ω ÷ 1999 Ω	1 Ω	
		Indication only

Insulation resistance, Insulation – S resistance (250 V_{DC}, 500 V_{DC})

Range	Resolution	Accuracy
0.00 MΩ ÷ 19.99 MΩ	0.01 MΩ	±(5 % of reading + 3 digits)
20.0 MΩ ÷ 49.9 MΩ	0.1 MΩ	
50.0 MΩ ÷ 199.9 MΩ	0.1 MΩ	Indication only

Differential leakage current (230 V_{AC})

Range	Resolution	Accuracy
0.00 mA ÷ 19.99 mA	0.01 mA	±(5 % of reading + 5 digits)

Touch leakage current (230 V_{AC})

Range	Resolution	Accuracy
0.00 mA ÷ 7.0 mA	0.01 mA	±(10 % of reading + 5 digits)

Substitute leakage current (30 V_{AC})

Range	Resolution	Accuracy
0.00 mA ÷ 9.99 mA	0.01 mA	±(5 % of reading + 3 digits)
10.0 mA ÷ 20.0 mA	0.1 mA	

(P)RCD testing (10 mA, 15 mA, 30 mA)

Range	Resolution	Accuracy
0 ms ÷ 300 ms (½xIΔN)	0.1 ms	±3 ms
0 ms ÷ 300 ms (IΔN)	0.1 ms	
0 ms ÷ 40 ms (5xIΔN)	0.1 ms	±1 ms

Power measurement (230 V_{AC})

Range	Resolution	Accuracy
0.00 kVA ÷ 4.00 kVA	0.01 kVA	±(5 % of reading + 3 digits)

Voltage TRMS measurement

Range	Resolution	Accuracy
80 ÷ 300 V	1 V	±(2 % of reading + 2 digits)

Clamp current

Range	Resolution	Accuracy
0.00 mA ÷ 9.99 mA	0.01 mA	±(5 % of reading + 10 digits)
10.0 mA ÷ 99.9 mA	0.1 mA	±(5 % of reading + 5 digits)
100 mA ÷ 999 mA	1 mA	±(5 % of reading + 5 digits)
1.00 A ÷ 9.99 A	0.01 A	±(5 % of reading + 5 digits)
10.0 A ÷ 16.0 A	0.1 A	±(5 % of reading + 5 digits)

Polarity test (<50 V_{AC})