

DIGITAL ANEMOMETER

C-LOGIC 280



HVAC



Industry



- TRMS measurements +
- 9 999 counts
- Air velocity : m/sc, f/min, km/h, miles/h, knots
- Air Flow : cf/min, m³/min, m³/sc
- Air velocity and air Flow measurement
- MAX/MIN values
- Data hold
- Auto-off display backlight and low battery display

CONTENTS



C-LOGIC 280

DIGITAL ANEMOMETER

General	
Display	9999 counts
Auto power off	✓
Flow Area Setting	✓
MAX / MIN	✓
Data Hold	✓
Display Backlight	✓
Low Battery Display	✓

UNITS	SCALE	RESOLUTION	ACCURACY
m/s	0.80~30.00 m/s	0.01 m/s	± (2.0% + 50 digits)
	30.00~40.00 m/s	0.01 m/s	As reference
km/h	2.88~108.0 km/h	0.01 km/h	± (2.0% + 50 digits)
	108.0~144.0 km/h	0.1 km/h	As reference
Ft/s	2.62~98.50 ft/s	0.01 ft/s	± (2.0% + 50 digits)
	98.5~131.2 ft/s	0.01 ft/s	As reference
Nautical miles./h	1.6~58.30 knots	0.01 knots	± (2.0% + 50 digits)
	58.30~77.70 knots	0.01 knots	As reference
Miles/h	1.8~67.20 miles/h	0.01 miles/h	± (2.0% + 50 digits)
	67.20~90.00 miles/h	0.01 miles/h	As reference
Ft/min	157.5~5900 ft/min	1 ft/min	± (2.0% + 50 digits)
	5900~7874 ft/min	2 ft/min	As reference

C-LOGIC 280

DIGITAL ANEMOMETER

Product Code Information	
SKU	CLOGIC280CBINT
EAN code	8435394747941
UPC code	810053671306
Pcs/export carton	20