

Function	Range	Accuracy
DC Voltage	60.00 mV...1000 V	From $\pm(0.4\%$ of reading + 5 digits) to $\pm(0.2\%$ of reading + 3 digits)
AC Voltage (50 Hz ~ 500 Hz)	60.00 mV...1000 V	$\pm(1.0\%$ of reading + 5 digits)
DC Current	600.0 μ A...8.00 A	From $\pm(0.5\%$ of reading + 5 digits) to $\pm(1.8\%$ of reading + 6 digits)
AC Current (50 Hz ~ 400 Hz)	600.0 μ A...8.00 A	From $\pm(1.0\%$ of reading + 3 digits) to $\pm(1.8\%$ of reading + 6 digits)
Diode Test	1.000V	$\pm(1.0\%$ of reading + 3 digits)
	Open-circuit voltage < 1.8 V DC, Test current 0.56 mA	
Resistance	600.0 Ω ... 60.00 M Ω	From $\pm(0.5\%$ of reading + 4 digits) to $\pm(1.2\%$ of reading + 4 digits)
Capacitance	60.00 nF...3000 μ F	From $\pm(1.5\%$ of reading + 5 digits) to $\pm(2.0\%$ of reading + 5 digits)
Temperature	-50 $^{\circ}$ C...1000 $^{\circ}$ C	$\pm(0.3\%$ of reading + 3 digits)
	-58 $^{\circ}$ F...1832 $^{\circ}$ F	$\pm(0.3\%$ of reading + 6 digits)
Frequency of digital equipment	5.00 Hz...1.000MHz	$\pm(0.003\%$ of reading + 2 digits)
Mains frequency	10 Hz...50kHz	$\pm(0.003\%$ of reading + 3 digits)
Power supply	2 x 1.5 V batteries, type AAA	
Overvoltage category	CAT IV / 300 V; CAT III / 600 V; CAT II / 1000 V	
Dimensions	161 x 80 x 50 mm	
Weight	340 g	