

| Function | Range | Accuracy |
|----------------------------|---|---|
| DC voltage | 400.0 mV ... 1000 V | from $\pm(0.3\%$ of reading + 4 digits) to $\pm(1.0\%$ of reading + 4 digits) |
| AC voltage (50 ... 500 Hz) | 400.0 mV ... 1000 V | from $\pm(1.5\%$ of reading + 5 digits) to $\pm(4.0\%$ of reading + 5 digits) |
| DC current | 400.0 μ A ... 10.00 A | from $\pm(1.2\%$ of reading + 3 digits) to $\pm(2.0\%$ of reading + 5 digits) |
| AC current | 400.0 μ A ... 10.00 A | from $\pm(1.5\%$ of reading + 4 digits) to $\pm(2.0\%$ of reading + 6 digits) |
| Diode test | Open-circuit voltage $<1.6 V_{DC}$, Test current 0.25 mA | |
| Resistance | 400.0 Ω ... 40.00 M Ω | from $\pm(0.6\%$ of reading + 4 digits) to $\pm(2.0\%$ of reading + 4 digits) |
| Temperature | -20 $^{\circ}$ C ... 300 $^{\circ}$ C | $\pm(2.0\%$ of reading + 3 $^{\circ}$ C) |
| Frequency | 50.00 Hz ... 1.000 MHz | $\pm(0.5\%$ of reading + 4 digits) |
| Capacitance | 500.0 nF ... 3000 μ F | $\pm(3.5\%$ of reading + 6 digits) |
| Power supply | 2 x 1.5 V batteries, type AAA | |
| Overvoltage category | CAT IV / 300 V; CAT III / 600 V; CAT II / 1000 V | |
| Dimensions | 198 x 97 x 55 mm | |
| Weight | 396 g | |