

Circuit breaker testing

Accessories

Contents

Cables	3
DCM – DualGround	9
Software.....	10
Application kits.....	11
Static and dynamic resistance measurement	13
Transducers	15
Linear	15
Rotary	15
Transducer accessories	16
Transducer mounting kits	17
Universal kits.....	17
Circuit breaker specific kits	18
Ready-to-use kits – Rotary	19
Transducer mounting accessories.....	19
Other.....	21
Connecting and mounting guidance.....	23
SDRM Hook-up examples and cable designations.....	23
DualGround - safe testing.....	24
Transducer mounting examples	25
First trip measurement.....	26



Megger

WWW.MEGGER.COM

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
Cables						
<i>Analogue Input XLR/Banana</i>	 <p data-bbox="687 611 1110 667">XLR female / 4 mm safety plugs, 1 m (3.3 ft). For customized analog transducer connection</p>	X	X	X	X	GA-00040
<i>Cable Analogue XLR/open ends</i>	 <p data-bbox="687 916 1023 943">XLR female / open ends, 1 m (3.3 ft)</p>	X	X	X	X	GA-00041
<i>Extension cable Analogue Input</i>	 <p data-bbox="687 1171 1086 1227">For analog input, XLR3 female / XLR3 male Analog cable EGIL/TM, 7.5 m (24.6 ft)</p>	X	X	X	X	GA-00042
<i>Transducer cable, XLR / IP / TS</i>	 <p data-bbox="687 1473 1007 1500">NOVOTECHNIC IP/TS, 1 m (3.3 ft)</p>	X	X	X	X	GA-00044
<i>Transducer cable, XLR / TLH / LWH</i>	 <p data-bbox="687 1753 1062 1780">NOVOTECHNIC TLH/LWH, 0.5 m (1.6 ft)</p>	X	X	X	X	GA-00049
<i>Transducer cable XLR / LWG</i>	 <p data-bbox="687 2033 1074 2060">NOVOTECHNIC LWG/M12, 0.5 m (1.6 ft)</p>	X	X	X	X	GA-00050

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
Cable Current clamp						
	For current clamp, BNC / XLR3, 0.3 m (1 ft)	X	X	X	X	GA-00140
Cable, extension EGIL Timing MAIN						
	Extension cable for time measurement of main contacts, XLR5 female / XLR5 male 10 m (32.8 ft)				X	GA-00150
	5 m (16.4 ft)				X	GA-00155
Cable, EGIL Timing						
	Timing 5 m (16.4 ft) XLR5 / 4 mm banana incl. clamps				X	GA-00160
Cable, EGIL Timing AUX						
	AUX1&2, timing 2 m (6.5 ft) XLR5 / 4 mm banana excl. clamps				X	GA-00170
Cable, EGIL Voltage sense						
	SDRM Voltage sense cable incl. clamps, 2 m (6.5 ft)				X	GA-00175
Cable set, Timing TM1800 AUX TM1700 AUX TM1600 MAIN TM1600 AUX						
	The cable sets consist of 8 cables with clamps and 4 mm stackable safety plugs. For timing of CB contacts.					
	5 m (16.4 ft)	X	X	X		GA-00231
	10 m (32.8 ft)	X	X	X		GA-00241
	15 m (49.2 ft)	X	X	X		GA-00251
	20 m (65.6 ft)	X	X	X		GA-00261
	25 m (82 ft)	X	X	X		GA-00271
	40 m (131 ft)	X	X	X		GA-00281

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
<p>SCA600/Coax. Cable</p> 		X	X	X		GA-00750
<p>Extension cable Analogue input</p> 	<p>XLR female/XLR male 1 m (3.3 ft)</p>	X	X	X	X	GA-00760
<p>Cable reel</p> 	<p>20 m (65.5 ft), 4 mm stackable safety plugs</p> <p>Black</p> <p>Red</p> <p>Yellow</p> <p>Green</p> <p>Blue</p>	X	X	X	X	GA-00840
<p>Cable Timing MAIN</p> 	<p>Timing M/R XLR3 male / banana, 5 m (16.4 ft), Length of the split portion (retractable sock), 2.4 m (8 ft) to 3.8 m (12 ft)</p>	X	X			GA-00850
<p>Extension cable Timing MAIN</p> 	<p>For Timing M/R modules, XLR3 male / XLR3 female, 10 m (32.8 ft)</p>	X	X			GA-00851
<p>Adapter for Doble digital transducer</p> 	<p>For Doble transd. (Use with GA-00895)</p>	X	X			GA-00867

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
Adapter for Siemens digital transducer						
	For Siemens digital transducer	X	X			GA-00868
Adapter for Vanguard digital transducer						
	For Vanguard transd. (Use with GA-00895)	X	X			GA-00869
Cable Timing AUX	 <p data-bbox="687 1070 970 1173"> Including: 4 Adapter for terminal block 4 Cable lug adapter 1 Cable, 5 m, (16.4 ft) </p>					
		X	X			GA-00870
Digital transducercable						
	For customized digital transducer connection RS422, SUB-D15 / open ends, 10 m (33 ft)	X	X			GA-00885
Digital transducer extension cable						
	RS422, SUB-D15 / SUB-D15, 10 m (33 ft)	X	X			GA-00888
Cable Digital TP1 and Rotary EIL						
	NOVOTECH Digital TP1 and Rotary Baumer EIL transducer cable, D-SUB 15 / M12					
	20 m (66 ft)	X	X			GA-00887
	10 m (33 ft)	X	X			GA-00889

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
Adapter for Elcon digital transducer	For using Leine & Linde 530 digital transducer, 10 m (33 ft)	X	X			GA-00890
Baumer digital cable						
	For using Baumer BDH16.05A3600-LO-B, digital transducer, 10 m (33 ft)	X	X			GA-00895
Heidenhein digital cable	Digital transducer cable, Heidenhein, 10 m (33 ft)	X	X			GA-00900
Ethernet cable, network	Cable for connection to network/LAN, RJ45	X	X			GA-00970
TM1700/1800 DCM extension cable	1 DCM extension cable, DIN 6, 10 m (33 ft) Old type	X	X			GA-00998
	1 DCM extension cable, DIN 7, 10 m (33 ft) Actual type. See "TM1700/1800 DCM Extension cable" on page 9	X	X			GA-00999
Open analog cable						
	For customized analog transducer connection, 1 m (3.3 ft)	X	X	X	X	GA-01000
Extension cable Analogue Input						
	For analog input, XLR3 female / XLR3 male Analog cable EGIL/TM, 10 m (33 ft)	X	X	X	X	GA-01005
Cable for AnaDig 10						
	Optional Cable for AnaDig 100, 1 m (3 ft)	X	X			GA-01008
Cable kit Control						
	Control kit for three phases Including: 5 Test clip 5 Adapter for terminal block 5 Cable lug adapter 5 5 m (16 ft) 2 0.25 m (10") 2 Jumper 1 Plastic box	X	X			GA-90002

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
HV Timing cable kit 	For Timing M/R modules, XLR3 male / XLR3 female 5 Cable, 10 m (32.8 ft) GA-00851	X	X			GA-90005
Connection kit for Control cables"	 <p><i>Including:</i></p> <ul style="list-style-type: none"> 5 Test clip 5 Adapter for terminal block 5 Cable lug adapter 1 Plastic box 	X	X	X	X	GA-90010

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
DCM – DualGround						
<i>DCM</i>	 <p>DCM TM1700 DualGround Timing</p> <p>3- channels Including: 1 DCM Upgrade cable kit CG-19180 X BL-59190</p> <p>6-channels Including: 2 DCM Upgrade cable kit CG-19180 X BL-59192</p>					
<i>TM1700/1800 DCM Upgrade cable kit</i>	 <p>Cables for 3 channels addition DualGround upgrade from 3 to 6 channels Length of the 2-cable portion, 1.5 m (5 ft) Including: 3 DCM cable, 12 m (39 ft) 6 Clamp</p>	X	X			CG-19180
<i>TM1700/1800 DCM Extension cable kit</i>	 <p>DualGround cable, DIN 7, extension for 3 channels 10 m (33 ft) (3 x GA-00999)</p>	X	X			CG-19181
<i>DCM - TM1800</i>	 <p>Module for TM1800</p> <p>DCM Module 3 DCM cables, 12 m (39 ft) DCM to Timing M/R cable GA-12900 6 Timing clamps KD-03040 Accessory bag GD-31040 X CG-19190</p> <p>DCM Module 6 DCM cables, 12 m (39 ft) DCM to Timing M/R cable GA-12900 12 Timing clamps KD-03040 Accessory bag GD-31040 X CG-19192</p>					
<i>DCM Span extension cable</i>	 <p>Cable to extend the span in the TM1700/1800 DCM BNC / BNC, 2 m (6.6 ft)</p>	X	X			GA-00720
<i>DCM Cable link</i>	 <p>DCM to Timing M/R</p>	X				GA-12900

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
Software						
CABA Win						
	For TM1700/1800, incl. Ethernet cross-over cable	X	X			CG-8000X
	For TM1600, incl. fiberoptics and USB interface			X		BL-8203X
	For EGIL, incl. USB cable				X	BL-8206X
	Upgrade to R04D	X	X	X	X	CG-8010X
	Upgrade to R05, including Test Plan Editor (TPE)	X	X	X	X	CG-8040X

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
Application kits						
<i>First trip kit</i>						
	For single operating mechanism, 1 + 3 clamps	X	X			BL-90700
	For three operating mechanisms, 3 + 3 clamps	X	X			BL-90710
<i>Synchro Switch Relay kit</i>						
	Synchronized Switching Relay test kit incl. accessories, software and cables (delivered in transport case)					
	SSR kit for TM 1700/1800	X	X			CG-91200
	SSR for TM1600 (incl. VD401)			X		BL-91200
<i>Transducer calibration kit</i>						
	Plate XB-39022 not included					
		X	X	X	X	XB-39095
<i>Vibration kit</i>						
	The Vibration kit extends TM1800/TM1700/TM1600 and CABA Win with the equipment and software required for recording and analyzing vibration signals at a circuit breaker. The kit includes the signal conditioning unit SCA606, the software CABA Win Vibration and one vibration channel. The vibration solution can be extended up to 6 channels.					
		X	X	X		BL-13090

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
<p>Vibration channel</p> 	<p>Additional vibration channel to be used together with the Vibration kit. Each Vibration channel includes accelerometer, accelerometer adapter, cables to SCA606 and cables to TM1800/TM1700/TM1600*.</p>	X	X	X		XB-32010

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
Static and dynamic resistance measurement						
SDRM201 EGIL	  GB-03430					
	Included accessories: SDRM Cable GB-03430 SDRM multi cable extension GA-12815 Voltage sense GA-00175 Voltage sense extension cable GA-00150 Current cable (red) GA-12820 Current cable (black) GA-12830 Clamps (2 pcs) KD-03040 Ground cable, 2.5 mm ² , 10 m (33 ft) GA-00208 Charger HC-04210 Accessory bag GD-31040 Case GD-00222					
SDRM202						
	Included accessories SDRM Cable for TM1700/1800 GB-03411 SDRM multi cable extension, 7.5 m (24.6 ft) GA-12815 Current cable, red, 2pcs, 3 m (9.8 ft) GA-12820 Current cable, black 2 pcs, 0.5 m (1.6 ft) GA-12830 Ground cable, 2.5 mm ² 10 m (33 ft) GA-00208 Charger HC-04210 Accessory bag GD-31040 Case GD-00222	X	X			CG-90200
	Pack of 3 units (CG-90200) for circuit breaker with 2 Breaks/Phase	X	X			CG-90230
	SDRM Cable for TM1600 GB-03421 SDRM multi cable extension, 7.5 m (24.6 ft) GA-12815 Current cable, red, 2 pcs, 3 m (9.8 ft) GA-12820 Current cable, black 2 pcs, 0.5 m (1.6 ft) GA-12830 Ground cable, 2.5 mm ² 10 m (33 ft) GA-00208 Charger HC-04210 Cable XLR/Banana 2 pcs. GA-00040 Accessory bag GD-31040 Case GD-00222					
	SDRM Cable for EGIL GB-03430 SDRM multi cable extension, 7.5 m (24.6 ft) GA-12815 Voltage sense cable, 2 m (6.5 ft) GA-00175 Voltage sense extension cable, 10 m (33 ft) GA-00150 Current cable, red, 2pcs, 3 m (9.8 ft) GA-12820 Current cable, black 2 pcs, 0.5 m (1.6 ft) GA-12830 Clamps (2 pcs) KD-03040 Ground cable, 2.5 mm ² 10 m (33 ft) GA-00208 Charger HC-04210 Accessory bag GD-31040 Case GD-00222			X		CG-90210
	SDRM Cable for EGIL GB-03430 SDRM multi cable extension, 7.5 m (24.6 ft) GA-12815 Voltage sense cable, 2 m (6.5 ft) GA-00175 Voltage sense extension cable, 10 m (33 ft) GA-00150 Current cable, red, 2pcs, 3 m (9.8 ft) GA-12820 Current cable, black 2 pcs, 0.5 m (1.6 ft) GA-12830 Clamps (2 pcs) KD-03040 Ground cable, 2.5 mm ² 10 m (33 ft) GA-00208 Charger HC-04210 Accessory bag GD-31040 Case GD-00222				X	CG-90220

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
SDRM202 Cable	SDRM Cable for TM1700/1800 Including: Accessory bag	X	X			GD-31040 CG-90205
	SDRM Cable for TM1600 Including: Accessory bag Cable XLR/Banana 2 pcs.			X		GD-31040 GA-00040 CG-90215
	SDRM Cable for EGIL Including: Voltage sense extension cable 10 m (33 ft) Accessory bag Voltage sense cable, 2 m (6.5 ft) Clamps 2 pcs)				X	GA-00150 GD-31040 GA-00175 KD-03040 CG-90225
Extension cable, SDRM201/202		X	X	X	X	GA-12810
Current cables and clamps for SDRM202		X	X	X	X	GA-12820
	Cable, black, 0.5 m (1.6 ft)	X	X	X	X	GA-12830
	Clamps (2 pcs)	X	X	X	X	KD-03040

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
Transducers						
Linear						
Analog						
<i>TLH-150</i>	150 mm (5.9") travel ¹⁾	X	X	X	X	XB-30016
<i>TLH-225</i>	225 mm (8.8") travel ¹⁾	X	X	X	X	XB-30017
<i>TLH-500</i>	500 mm (19.7") travel ¹⁾	X	X	X	X	XB-30020
<i>TLH-750</i>	750 mm (29.5") travel ¹⁾	X	X	X	X	XB-30022
<i>TLH-1000</i>	1000 mm (39.4") travel ¹⁾	X	X	X	X	XB-30023
	¹⁾ Including cable, 0.5 m (20") GA-00049					
<i>LWG 150</i>	150 mm (5.9") travel ²⁾	X	X	X	X	XB-30116
<i>LWG 225</i>	225 mm (8.8") travel ²⁾	X	X	X	X	XB-30117
<i>LWG 500</i>	500 mm (19.7") travel ²⁾	X	X	X	X	XB-30120
	²⁾ Including cable, 0.5 m (20") GA-00050					
<i>TS 150</i>	150 mm (5.9") travel ³⁾	X	X	X	X	XB-30030
<i>TS 50</i>	50 mm (1.9") travel ³⁾	X	X	X	X	XB-30031
<i>TS 25</i>	25 mm (1") travel ³⁾	X	X	X	X	XB-30033
	³⁾ Including cable, 1 m (39") GA-00044					
Digital						
<i>Linear transducer TP1 300 mm</i>	NOVOTECHNIC TP1 (Highspeed design for Megger) 300 mm (11.8") travel Including: Cable 10 m (33 ft)	X	X			XB-39140
	Cable 20 m (66 ft)	X	X			XB-39145
<i>Linear transducer TP1 500 mm</i>	NOVOTECHNIC TP1 (Highspeed design for Megger) 500 mm (19.7") travel Including: Cable 10 m (33 ft)	X	X			XB-39150
	Cable 20 m (66 ft)	X	X			XB-39155
The above transducers are also available in other lengths, please contact Megger for more information.						
<i>Touchless linear digital transducer (kit)</i>	 Including: Magnetic band, 2 m (6 ft), XB-39250 Touchless linear digital transducer, SIKO, XB-39237 Cable, 10 m (33 ft), GA-00889 Clamping base, XB-39014 Flexible arm, XB-39012	X	X			XB-39230
Rotary						
Analog						

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
<p>Transducer kit</p> 	<p>Novotechnic IP6501 Including: Cable, 1 m (39"), Flex coupling, 6 mm Hexagon wrench</p>	X	X	X	X	XB-31010
<p>Digital</p>	<p>Transducer kit</p>		<p>Baumer EIL580-SC10.5RH.03600.A Including: Flex coupling, 10/6 mm Hexagon wrench With Cable, 10 m (33 ft) With Cable, 20 m (66 ft)</p>	X	X	XB-39130
<p>Transducer accessories</p>	<p>Slider</p>		<p>Slider for linear transducer TP1</p>	X	X	XB-39199

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
Transducer mounting kits						
Universal kits						
<i>TLH/LWG kit</i>						
	For use with linear transducers (TLH/LWH)	X	X	X	X	XB-39065
<i>Transducer kit 500/600 mm</i>						
	Single phase, Analog, Linear, 500 mm (19.7")	X	X	X	X	XB-40101
	Single phase, Analog, Linear, 600 mm (23.6")	X	X	X	X	XB-40102
	Single phase, Digital, Linear, 500 mm (19.7")	X	X			XB-40105
	Single phase, Digital, Linear, 600 mm (23.6")	X	X			XB-40106
<i>Transducer kit 300 mm</i>						
	Single phase, Analog, Linear, 300 mm (11.8")	X	X	X	X	XB-40103
	Single Phase, Digital, Linear, 300 mm (11.8")	X	X			XB-40107
						
	3 phase, Analog, Linear, 300 mm (11.8")	X	X	X		XB-40104
	3 Phase, Digital, Linear, 300 mm (11.8")	X	X			XB-40108
<i>Transducer kit w/o transducer</i>	Single phase, Analog, Linear, 500-600 mm (19.7"-23.6")	X	X	X	X	XB-40110
	Single phase, Analog, Linear, 300 mm (11.8")	X	X	X	X	XB-40111
	3 phase, Analog, Linear, 300 mm (11.8")	X	X	X		XB-40112
	Single Phase, Digital, Linear, 500-600 mm (19.7"-23.6")	X	X			XB-40113
	Single Phase, Digital, Linear, 300 mm (11.8")	X	X			XB-40114
	3 Phase, Digital, Linear, 300 mm (11.8")	X	X			XB-40115
<i>Rotary transducer mounting kit</i>						
	For transducers XB-31010 and XB-39130					
	Including:					
	Clamping base	XB-39014				
	Flexible arm	XB-39021				
	Holder for angular transducer	XB-39022				
	Plastic transport case	XB-39023				
	Adapter M6/6 2 Nuts M6	XB-39025				
	Adapter M8/6 2 Nuts M8	XB-39026				
	Adapter M10/6 2 Nuts M10	XB-39027				
	Adapter M12/6 2 Nuts M12	XB-39028				
Holder for dig. rotary EIL and linear LWG, Ø 36 mm	XB-39005	X	X	X	X	XB-51010

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
<p><i>Universal transducer mounting kit</i></p> 	<p>For linear and rotary transducers Including: Magnetic base XB-39013 Clamping base XB-39014 Flexible arm XB-39021 Holder for angular transducer XB-39022 Plastic transport case XB-39023 Adapter M6/6 2 Nuts M6 XB-39025 Adapter M8/6 2 Nuts M8 XB-39026 Adapter M10/6 2 Nuts M10 XB-39027 Adapter M12/6 2 Nuts M12 XB-39028 Universal support XB-39029 Holder for dig. rotary EIL and linear LWG, Ø 36 mm XB-39005</p>					XB-51020
<p><i>AnaDig 100</i></p> 	<p>Analog to Digital converter for transducers</p>	X	X			XB-51050
<p><i>Universal adapter for rotary transducer</i></p> 	<p>Universal adapter to breaker and drive types HPL/BLG 3AP1FG</p>	X	X	X	X	XB-51060
Circuit breaker specific kits						
<p><i>HPL kit (ABB)</i></p> 	<p>For use on ABB HPL circuit breakers</p>	X	X	X	X	XB-39080
<p><i>BLG kit (ABB)</i></p> 	<p>For use on ABB mechanisms BLG 352, 352C, 1002 and 1002A</p>	X				XB-39085
<p><i>LTB kit (ABB)</i></p> 	<p>For use on ABB LTB circuit breakers with 3-column stand</p>	X	X	X	X	XB-39090
<p><i>LTB Kit (ABB)</i></p>	<p>Including: Mounting kit XB-51010 Software conversion table BL-8730X Universal adapter for rotary transducer XB-51060</p>	X	X	X	X	XB-61010
<p><i>HPL/BLG Kit (ABB)</i></p>	<p>Including: Mounting kit XB-51010 Software conversion table BL-8720X Universal adapter for rotary transducer XB-51060</p>	X	X	X	X	XB-61020

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
AHMA Kit (ABB)	 <p>3-Phase Diagnostic Set for ABB drive mechanism type AHMA 4/8 Including: 3 Transducers 3 Adapter cable Mounting details Transport case</p>					
	GA-00044	X	X	X		XB-61030
HMB Kit (ABB)	 <p>For drive mechanism type HMB 4/8 Three phase set complete in case Including: 3 PES-HMB8 Transducers 3 Adapter cable 1 Alu transport case 3 Calibration Certificates</p>					
	GA-00055 GD-00766	X	X	X		XB-61040
Ready-to-use kits – Rotary						
Analog						
1-phase kit	Incl. transducer XB-31010, mounting kit XB-51010	X	X	X	X	XB-71010
3-phase kit	Incl. 3 x 1-phase kits XB-71010	X	X	X		XB-71013
Digital						
1-phase kit	Including: Transducer XB-39130 Mounting kit XB-51010 With Cable, 10 m (33 ft)	X	X			XB-71020
	With Cable, 20 m (66 ft)	X	X			XB-71022
3-phase kit	Including: 3 x 1-pase kits XB-71020	X	X			XB-71023
	Including: 3 x 1-pase kits XB-71022	X	X			XB-71025
Transducer mounting accessories						
Holder for transducer	 <p>Holder for dig. rotary Baumer EIL and linear LWG, Ø 36 mm</p>	X	X			XB-39005
Flexible arm		X	X	X	X	XB-39012
Switch magnetic base		X	X	X	X	XB-39013
Clamping base		X	X	X	X	XB-39014

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
Flexible arm		X	X	X	X	XB-39021
Holder for transducer		X	X	X	X	XB-39022
Flex coupling		X	X	X	X	XB-39030
Flex coupling		X	X			XB-39032
Thread adapter kit	 <p data-bbox="687 1077 1094 1256"> Imperial / metrics adapter kit for TLH / TP1 Including: 1 nut metrics, M5 1 spacer nut, M5 / UNF 10-32 1 spacer nut, M5 / UNC 1/4-20 1 nut, UNF 10-32 1 nut, UNC 1/4-20 </p>	X	X	X	X	XB-39036
Distance screw		X	X			XB-39160
Rod for digital transducer TP1		X	X	X	X	XB-39193


Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
Other						
<i>Dolphin clamps</i>						
	Black	X	X	X	X	40-083220
	Red	X	X	X	X	40-08322
<i>Timing clamp</i>						
	Timing clamp for bolt head	X	X	X	X	53-31800
<i>Cable organizer</i>						
	Hook-and-loop straps, 10 pcs.	X	X	X	X	AA-00100
<i>Long term monitoring</i>						
<i>LTM1</i>	EPRM to be mounted in the TM1600 Starts measurement when there is a change at any of the time-measuring inputs.			X		BL-80010
<i>LTM2</i>	Functions in the same way as a standard TM1600, but returns automatically to the READY state after measurement.			X		BL-80011
<i>VD401</i>						
	Voltage divider, ratio 400/1 (for TM1600 and EGIL with analog channel)			X	X	BL-90070
<i>USB to fiber adapte</i>						
	CABA Hardware USB to fiber adapter			X		BL-90165
<i>Current</i>						
	AC/DC clamp/clip-on/current probe, Fluke 80i-110s Current sensor kit 1 channel (Fluke 80i-110s incl. cable GA-00140)	X	X	X	X	BL-90600
	Current sensor kit 3 channels 3 x (Fluke 80i-110s incl. cables GA-00140)	X	X	X		BL-90610
<i>Temperature sensor</i>						
	With the temperature sensor the ambient temperature is automatically recorded with each measurement and stored together with the test result. The temperature becomes a parameter in CABA Win. Suitable cable is the Analog cable, 10 m GA-01005. Range: -20°C to +50°C (-4°F to +122°F) Resolution: 0.5°C (0.9°F)	X				CG-90070

Item	Description	TM1800	TM1700	TM1600	EGIL	Art. No.
 <p>Thermopaper, for Fujitsu</p>	114 mm, 30 m			X	X	GC-00030
	Box/24 pcs			X	X	GC-00032
 <p>Thermopaper</p>	114 mm, Ø 40 mm	X				GC-00040
	Soft case					
 <p>Soft case</p>	Made from sturdy nylon fabric	X	X			GD-00340
	Clamp					
 <p>Clamp</p>						
	Clamps					
 <p>Clamps</p>	Multipurpose Timing clamp, black, 4 mm banana	X	X	X	X	KD-03040
	 <p>Clamps</p>	Multipurpose Timing clamp, red, 4 mm banana	X	X	X	X
 <p>Ferrite kit</p>		Accessory for timing of GIS circuit breakers using TM1800 with DualGround™				
	<p>Including:</p> <ul style="list-style-type: none"> C-shape ferrite 7 XB-40010 I-shape ferrite 4 XB-40020 Round ferrite 4 30-67090 Hook and loop fastener 4 09-10140 Transport case GD-00440 User's Manual ZP-CG04E 	X	X			XB-40090


For more information about optional accessories please contact Megger

Connecting and mounting guidance


SDRM Hook-up examples and cable designations




Timing cable is included with the TM1800 timing module. Transducer cable is selected together with the the type of transducer used.



Timing cable is included with the TM1700. Transducer cable is selected together with the the type of transducer used.



Timing cable is an optional accessory to TM1600. Transducer cable is selected together with the the type of transducer used.




Transducer cable is selected together with the the type of transducer used.

DualGround - safe testing


The best way to provide safety in circuit breaker testing is to keep both sides of the circuit breaker grounded throughout the test. This will also make the test faster and easier. Minimum time shall be spent in the substation and focus shall be on the test rather than the equipment.

One side grounded



Conventional vs. DualGround	
Site preparation (isolate work area, apply safety ground, issue permit to work)	Site preparation (isolate work area, apply safety ground, issue permit to work)
Hook up test equipment. Issue sanction for test	Hook up test equipment. Issue sanction for test
Authorised person removes the ground	Risky step left out
Perform testing	Safe testing with both sides grounded
Authorised person applies ground	Risky step left out
Cancel sanction for test. Disconnect test equipment	Cancel sanction for test. Disconnect test equipment
Site closing (cancel permit to work, disconnect ground)	Site closing (cancel permit to work, disconnect ground)


Both sides grounded



Transducer mounting examples


Analog transducer mounted on a distribution circuit breaker

1. Clamping base
2. Flexible arm
3. Holder angular transducer
4. Novotechnik IP6501
5. Flex coupling
6. Bolt adapter



Analog transducer mounted on a distribution circuit breaker

1. Magnetic base
2. Flexible arm
3. Holder angular transducer
4. Novotechnik IP6501
5. Flex coupling
6. Bolt adapter



First trip measurement

When a fault occurs on a transmission or distribution line, the mission for the circuit breaker is to open the circuit to isolate the fault from the power source. A quick interruption of the current will avoid or limit damage to expensive equipment caused by the high fault currents.

Why capture first trip

Testing circuit breakers can be done in many ways, but one of the most common is timing of the main contacts, which gives a direct indication of the trip time. A typical procedure for performing a timing test on a circuit breaker is:

1. Open the CB
2. Disconnect the CB by opening the disconnecter switches
3. Ground the CB
4. Perform the timing test

Will the timing tests show the true trip time? Well, not necessarily. Consider a circuit breaker that has been in service without operating for many months, even years, before it was taken out of service for testing. It might then be suffering from a lack of or dried grease and maybe corrosion in its bearings. These problems can, and most probably will, slow down the first operation.

The problem with this procedure is that the CB has been operated at least once before the testing procedure begins. This operation might be all it takes to “shake off” any corrosion problems or sticky bearings and bring the breaker’s trip time up to standard. So when the actual timing test is performed, no problem exists and the service engineer thinks the breaker is in good shape and no further service is needed. Some months later the corrosion is back and when a fault occurs the CB does not trip fast enough, or maybe not at all. This is why it is important to capture the first operation to reveal any problems with the CB.

Perform a first trip test

A good and time effective way to check the condition of a circuit breaker is to document its behavior at the first open operation after it has been idle for long time. The measurement and connections to the CB are carried out while it is still in service. The only way to measure the currents in a safe way is to use current clamps. For the coil current, either one or three clamps are needed depending on the number of operating mechanisms. The clamps shall be of DC type in order to manage all types of coils.

Connecting current clamps to the CT’s secondary winding makes it possible to check the transition of the line currents to zero during the opening of the CB contacts as well as the synchronization of the opening times on the three phases.

The equipment needed for a first trip measurement depends on the configuration of the circuit breaker. All the connections are made inside the control cabinet.




Figure 1. Point for measuring coil current and control voltage.




Figure 2. Points for measuring the line currents. Since the CB is in service, the conventional way with leads across the CB cannot be used. Instead, three current clamps are used on the secondary side of the current transformer for each phase. For ordering information, see “First trip kit” on page 11.

Your "One Stop" Source for all your electrical test equipment needs

- Battery Test Equipment
- Cable Fault Locating Equipment
- Circuit Breaker Test Equipment
- Data Communications Test Equipment
- Fiber Optic Test Equipment
- Ground Resistance Test Equipment
- Insulation Power Factor (C&DF) Test Equipment
- Insulation Resistance Test Equipment
- Line Testing Equipment
- Low Resistance Ohmmeters
- Motor & Phase Rotation Test Equipment
- Multimeters
- Oil Test Equipment
- Portable Appliance & Tool Testers
- Power Quality Instruments
- Recloser Test Equipment
- Relay Test Equipment
- T1 Network Test Equipment
- Tachometers & Speed Measuring Instruments
- TDR Test Equipment
- Transformer Test Equipment
- Transmission Impairment Test Equipment
- Watthour Meter Test Equipment
- STATES® Terminal Blocks & Test Switches
- Professional Hands-On Technical and
- Safety Training Programs

Megger is a world leading manufacturer and supplier of test and measurement instruments used within the electric power, building wiring and telecommunication industries.

With research, engineering and manufacturing facilities in the USA, UK, Germany and Sweden, combined with sales and technical support in most countries, Megger is uniquely placed to meet the needs of its customers worldwide.

Megger is certified according to ISO 9001 and 14001. Megger is a registered trademark.

Megger Group Limited
UNITED KINGDOM
Dover, Kent CT17 9EN
ENGLAND

- AUSTRALIA
- CANADA
- CHINA
- FRANCE
- GERMANY
- INDIA
- INDONESIA
- JAPAN
- KINGDOM OF BAHRAIN
- KOREA
- MALAYSIA
- PAKISTAN
- PHILIPPINES
- RUSSIA
- SINGAPORE
- SOUTH AFRICA
- SPAIN
- SWEDEN
- SWITZERLAND
- TAIWAN
- THAILAND
- UNITED ARAB EMIRATES
- USA
- VIETNAM



Megger

WWW.MEGGER.COM

Postal address:

Megger Sweden AB
Box 724
SE-182 17 DANDERYD
SWEDEN

Visiting address:

Megger Sweden AB
Rinkebyvägen 19
SE-182 36 DANDERYD
SWEDEN

T +46 8 510 195 00 seinfo@megger.com
F +46 8 510 195 95 www.megger.com