

### 3-001-R001 / R002

## SF<sub>6</sub> gas refilling device

**For reliable refilling of SF<sub>6</sub> gas by overpressure**

3-001-R001

**SF<sub>6</sub> gas refilling device**

Mobile as cylinder cart with **wire-braided hoses**

3-001-R002

**SF<sub>6</sub> gas refilling device**

Mobile as cylinder cart with **rubber hoses**

Refilling device as cylinder cart for comfortable on board carrying of a gas bottle. The primary gauge of the pressure reducer displays the bottle pressure in bar, psi and kPa, the secondary gauge indicates the desired filling pressure to be set easily by means of the handle. The bottle pressure can be reduced to the desired filling pressure by the integrated pressure reducer.

During the refilling process emissions are avoided by self-closing couplings.



- Stable frame
- Available as accessories for the world's most commonly used bottle connections
- Hose reel
- Self-closing couplings prevent emissions
- Change of couplings feasible without gas loss

3-001-R001 / 3-001-R002

**SF<sub>6</sub> gas refilling device**

**Technical data:**

Dimensions: L 480 mm, W 540 mm, H 1,360 mm
Weight: 30 kg

**Standard equipment for both versions:**

SF <sub>6</sub> bottle connection W 21.8 x 1/14"
Ball valve with hand wheel
6 m long hose DN8
Pressure reducer for SF <sub>6</sub> (0 up to 10 bar), indication in bar / psi / kPa
DILO coupling tongue parts DN8 and DN20
Paint: orange (RAL 2004)
2 operating manuals in 3 languages (German / English / French)

**Optional accessories at an extra charge:**

SF <sub>6</sub> bottle connection with 0.96" Whitworth left-handed thread	<b>3-334-R001 P</b>
SF <sub>6</sub> bottle connection with G 5/8 thread	<b>3-315-R001 P</b>
English SF <sub>6</sub> bottle connection with G 5/8 thread	<b>3-245-R003 P</b>
Additional operating manual on CD-ROM	<b>6-0004-R213</b>

**Packing:**

Packing for 3-001-R001 / 3-001-R002	<b>3-262-R001-C</b>
-------------------------------------	---------------------