

Power supply	230V ac $\pm 10\%$, 50Hz $\pm 5\%$ or 60Hz $\pm 5\%$ 115V ac $\pm 10\%$, 50Hz $\pm 5\%$ or 60Hz $\pm 5\%$ 350 VA max
Test signal	Voltage: 0 to 6,000 VDC Short-circuit current: 0 to 5 mA
Measurement ranges	Voltage: 0 to 6,000 V Accuracy: $\pm 2\%$. Front panel LED indicator. Current: 0 to 5.12 mA (three-scale auto-range) Resolution: 1 nA Accuracy: $\pm 1\%$ DC Capacitance: 10 nF to 10 mF $\pm 5\%$ AC Capacitance: 10 nF to 10 mF $\pm 5\%$ Humidity: 10% to 90%. Accuracy: $\pm 10\%$ Temperature: -10°C to 70°C. Accuracy: $\pm 2\%$
Working conditions	Temperature: 10°C - 50°C Humidity: 10% - 75%, non-condensating
Storage	Temperature: 5°C - 75°C Humidity: 5% - 80%, non-condensating
Physical dimensions	19" x 3U rack Depth: 40 cm - Wide: 45 cm - High: 13.5 cm Weight: 9 Kg
Test leads	Long: 2 x 5 m Weight: 2 x 6 Kg