



983

Small hot plate, 35°C to 350°C

The small hot plate 983 is a lightweight portable calibration system designed for surface mounted sensors. The temperature range is from 35°C to 350°C, which is set by an advanced, but easy to use temperature controller. The sensor to be tested is simply placed on the surface, for higher accuracy a calibrated surface sensor can be placed alongside and the two compared.

- Low cost portable hot plate
- Stable to  $\pm 0.1^{\circ}\text{C}$
- PC interface and software

## Description

The small hot plate 983 is a lightweight portable calibration system designed for surface mounted sensors. The flat surface plate is made from precision-machined Aluminium. The sensor to be tested is simply placed on the surface, for higher accuracy a calibrated surface sensor can be placed alongside and the two compared.

Good thermal contact is ensured by the flat disc that is recessed to allow the optional use of a heat transfer paste or fluid. Uniform heat distribution is achieved with a flat spiral heater clamped to an integrating block below the surface of the plate. The typical accuracy that can be achieved is  $1^{\circ}\text{C}$  but this will be influenced by the type of sensor to be calibrated.

The internal control sensor is located immediately below the plate's surface.

A protective cover that can fit over the block is included along with a comprehensive handbook.

The temperature range is from 35°C to 350°C, which is set by an advanced, but easy to use temperature controller. The controller has 0.01 resolution below 100°C ( $0.1^{\circ}\text{C}$  above 100°C).

# Specifications

Temperature range	35°C to +350°C
Stabilization time	10 min
Cooling time	350°C to 100°C: 125 min
Heating time	50°C to 350°C: 20 min
Uncertainties	Dependant on sensors and method of use $\pm 1^\circ\text{C}$ typical
Calibration volume	Flat plate 71 mm diameter

## General specifications

Size	115 x 230 x 225 mm
Weight	3.9 kg
Display	Resolution: 0.01 to 99.99 and 0.1 to 100.0 / 350.0 Units: °C, °F, K
Power supply	100 / 115 V (50/60 Hz) or 200 / 230 V (50/60 Hz) 200 Watts
Communication ports	RS 232

# Models and accessories

## Instrument:

983                      Surface sensor calibrator, 35°C to 350°C

Delivered in standard with:

- Protective cover
- Cal Notepad software
- Serial communication cable
- User manual
- Traceable certificate
- Please specify supply voltage required at the order: 100 / 115 V (50/60 Hz) or 200 / 230 V (50/60 Hz)

## Packing information:

Size                      115 x 230 x 225 mm

Weight without packing   3.9 kg