

33XR-A

Display	LCD, 3999 digits	
Tensiune CA	0,1 mV...750 V	$\pm(1,5\% \text{ rdg} + 4 \text{ digits}) @ 45 \text{ Hz} \dots 500 \text{ Hz}$
Tensiune CC	0,1 mV...1000V	$\pm(0,7\% \text{ rdg} + 1 \text{ digit}) @ 10 \text{ M}\Omega$
Curent CA	0,1 μA ...10A	$\pm(1,5\% \text{ rdg} + 4 \text{ digits}) @ 45 \text{ Hz} \dots 500 \text{ Hz}$
Curent CC	0,1 μA ...10A	$\pm(1,0\% \text{ rdg} + 1 \text{ digit})$
Rezistentă	0,1 Ω ...4 M Ω	$\pm(1\% \text{ rdg} + 4 \text{ digits})$
Continuitate	R < 35 Ω	
Frecvență	10,00 Hz...1 MHz	$\pm(0,1\% \text{ rdg} + 3 \text{ digits})$
Capacitanță	4,000 nF...4,000 mF	$\pm(5\% \text{ rdg} + 10 \text{ digits})$
Temperatură	-20°C...1000°C	$\pm(2\% + 4^\circ\text{C})$
Clasa	CAT III/600V, CAT II/1000V	
Certificare	EN 61010, IEC 61010	
Baterie	1 x 9V	
Dimensiuni	196 x 92 x 60 mm.	
Greutate	~ 400 g. (incl. baterie)	