

35XP-A

Display	LCD, 3999 digiti	
Tensiune CA	0,1 mV...750 V	$\pm(1,5\% \text{ rdg} + 5 \text{ digiti}) @ 45 \text{ Hz} \dots 500 \text{ Hz}$
Tensiune CC	0,1 mV...1000V	$\pm(0,5\% \text{ rdg} + 1 \text{ digit})$
Curent CA	0,1 μA ...2A	$\pm(1,5\% \text{ rdg} + 5 \text{ digiti}) @ 45 \text{ Hz} \dots 500 \text{ Hz}$
Curent CC	0,1 μA ...2A	$\pm(1\% \text{ rdg} + 2 \text{ digiti})$
Rezistenta	0,1 Ω ...40 M Ω	$\pm(1\% \text{ rdg} + 4 \text{ digiti})$
Continuitate	R < 25 Ω	
Frecventa	10,00 Hz...1 MHz	$\pm(0,1\% \text{ rdg} + 3 \text{ digiti})$
Capacitanta	4,000 nF...4,000 mF	$\pm(5\% \text{ rdg} + 30 \text{ digiti})$
Temperatura	-20°C...1000°C	$\pm(2,0\% + 4^\circ\text{C})$
Clasa	CAT III/300 V, CAT II/600V	
Certificare	EN 61010, IEC 61010	
Baterie	1 x 9V	
Dimensiuni	155 x 72 x 32 mm.	
Greutate	~ 210 g. (incl. baterie)	