

		AM-510-EUR
Display		3999 digiti
Tensiune AC	Domeniu	1 mV...600V
	Precizie	$\pm (1.0 \% \text{ rdg.} + 3 \text{ digiti})$
	Domeniu frecvente	45 Hz...400 Hz
Tensiune CC	Domeniu	1 mV...600V
	Precizie	$\pm (0.8 \% \text{ rdg.} + 1 \text{ digit})$
	Rezistenta input	10 M Ω
Curent AC	Domeniu	0.1 μ A...10A
	Precizie	$\pm (1.2 \% \text{ rdg.} + 2 \text{ digiti})$
	Domeniu frecvente	45 Hz...400 Hz
Curent CC	Domeniu	0.1 μ A...10A
	Precizie	$\pm (1.0 \% \text{ rdg} + 2 \text{ digiti})$
Rezistenta	Domeniu	0.1 Ω ...40 M Ω
	Precizie	$\pm (1.2 \% \text{ rdg.} + 2 \text{ digiti})$
Continuitate		$R < 10 \Omega$
Capacitati	Domeniu	10 pF...100,0 μ F
	Precizie	$\pm (3 \% \text{ rdg.} + 5 \text{ digiti})$
Frecventa	Domeniu	1,00 Hz...10 MHz
	Precizie	$\pm (0.1 \% \text{ rdg.} + 4 \text{ digiti})$
Clasa		CAT III / 600V
Siguranta		EN 61010, IEC 61010
Alimentare		9 V
Dimensiuni		182 x 90 x 45 mm
Greutate		354 g (incl. baterie)