

		AM-540-EUR
Display		5999 digiti
Tensiune AC	Domeniu	1 mV...1000V
	Precizie	$\pm (1.0 \% \text{ rdg.} + 3 \text{ digits})$
	Domeniu frecvente	45 Hz...1 kHz
Tensiune CC	Domeniu	0.1 mV...1000 V
	Precizie	$\pm (0.5 \% \text{ rdg.} + 2 \text{ digits})$
	Rezistenta input	10 M Ω
Curent AC	Domeniu	0.1 μ A...10A
	Precizie	$\pm (1.2 \% \text{ rdg.} + 2 \text{ digits})$
	Domeniu frecvente	45 Hz...1 kHz
Curent CC	Domeniu	0.1 μ A...10A
	Precizie	$\pm (1.0 \% \text{ rdg} + 2 \text{ digits})$
Rezistenta	Domeniu	0.1 Ω ...60 M Ω
	Precizie	$\pm (1.2 \% \text{ rdg.} + 2 \text{ digits})$
Continuitate		$R < 10 \Omega$
Capacitati	Domeniu	60,00 nF...60 mF
	Precizie	$\pm (3 \% \text{ rdg.} + 5 \text{ digits})$
Frecventa	Domeniu	1,00 Hz...60 MHz
	Precizie	$\pm (0.1 \% \text{ rdg.} + 3 \text{ digits})$
Temperatura	Domeniu	-40...1000 $^{\circ}$ C
	Precizie	$\pm (1.0 \% \text{ rdg.} + 8 \text{ digits})$
Clasa		CAT IV / 600V, CAT III / 1000V
Siguranta		EN 61010, IEC 61010
Alimentare		9 V
Dimensiuni		182 x 90 x 45 mm
Greutate		354 g (incl. baterie)