



Model	PM51A	PM55A
		
Display	4000 digiti	6000 digiti
Tensiune CA	0,001 V...600 V	0,001 V...600 V
Precizie	(2,0% + 5 D)	(1,5% + 5 D)
Frecventa	50 Hz...500 Hz	50 Hz...60 Hz
Tensiune CC	0,1 mV...600 V	0,001 mV...450 V
Precizie	(1,0% + 2 D)	(0,5% + 3 D)
Curent CA	—	0,1 μ A...2000 μ A
Precizie	—	(1,5% + 3 D)
Frecventa	—	50 Hz...60 Hz
Curent CC	—	0,1 μ A...2000 μ A
Precizie	—	(1,2% + 3 D)
Rezistenta	0,1 Ω ... 40 M Ω	0,1 Ω ... 6 M Ω
Test dioda	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Test continuitate	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Capacitanta	0,1 nF...3000 μ F	0,1 nF...100,0 μ F
Frecventa	5 Hz...1 MHz	10 Hz...30,00 kHz
Temperatura	—	—
Automatic	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Manual	—	—
Data hold	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Min/Max	—	—
Varf	—	—
Valoare relativa	—	—
Auto Power Off	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Baterie	1 x 3 V	1 x 3 V
Clasa	CAT III / 300 V, CAT II / 600 V	CAT III / 300 V, CAT II / 600 V
	Card format	Card format, Detectie tensiune non-contact Voltect™, Holster protectiv din silicon