

PM55A

Display	LCD, 6000 digiti	
Tensiune CA	0,1 mV...600 V	$\pm(1,5\% \text{ rdg} + 5 \text{ digiti}) @ 50 \text{ Hz} \dots 60 \text{ Hz}$
Tensiune CC	0,1 mV...450V	$\pm(0,5\% \text{ rdg} + 3 \text{ digiti})$
Curent CA	0,1 μA ...2000 μA	$\pm(1,5\% \text{ rdg} + 3 \text{ digiti}) @ 50 \text{ Hz} \dots 60 \text{ Hz}$
Curent CC	0,1 μA ...2000 μA	$\pm(1,2\% \text{ rdg} + 3 \text{ digiti})$
Rezistenta	0,1 Ω ...6000 M Ω	$\pm(1,2\% \text{ rdg} + 6 \text{ digiti})$
Continuitate	R < 175 Ω	
Frecventa	10,00 Hz...30,00 kHz	$\pm(0,5\% \text{ rdg} + 4 \text{ digiti})$
Capacitanta	0,1 nF...100,0 μF	$\pm(3,5\% \text{ rdg} + 6 \text{ digiti})$
Temperatura	-20°C...1000°C	$\pm(2,0\% + 4^\circ\text{C})$
Clasa	CAT III/300 V, CAT II/600V	
Certificare	EN 61010, IEC 61010	
Baterie	1 x 3V	
Dimensiuni	113 x 53 x 10 mm.	
Greutate	~ 78 g. (incl. baterie)	