

| Model                           | 1693  | 1694   |
|---------------------------------|---|--------|
| Variable Output Voltage         | 1-15 V  | 1-30 V |
| Output Current                  | 60 A  | 30 A   |
| Rated Auxiliary Output Current  | 5 A   | 3 A    |
| Ripple and Noise                | 40 mVpp   |        |
| Load Regulation                 | 0.1% + 5 mV   |        |
| Line Regulation                 | 0.05% + 3 mV  |        |
| Input Voltage                   | 100-240 VAC, 50Hz/60Hz  |        |
| Efficiency                      | >85%  |        |
| Dynamic Power Factor Correction | >0.97 at optimal load   |        |
| Voltmeter and Ammeter Display   | 3-digit LED displays  |        |
| Meter Accuracy                  | +/- 1% + 1 count  |        |
| Indicator                       | Green LED for power on/off indication<br>Red LED for overload/short circuit indication                                  |        |
| Special Features                | Analog Remote Control & Remote Sense  |        |
| Cooling Method                  | Variable speed thermostatically controlled fan  |        |
| Operating Temperature           | 32 °F to 104 °F (0 °C to 40 °C), ≤ 80% R.H.   |        |
| Storage Temperature             | 5 °F to 158 °F (-15 °C to 70 °C), ≤ 85% R.H.  |        |
| Protections                     | Overload (Constant Current Limiting), Short Circuit, OTP (Overtemperature Protection), and OVP (Overvoltage Protection) |        |
| Approvals                       | CE-EMC: EN 55022 CE-LVD:EN 60950  |        |
| Dimension (W x H x D)           | 8.66" x 4.33" x 14.17" (220 x 110 x 360 mm)   |        |
| Weight                          | 12.8 lbs (5.8 kg)   |        |

**One Year Warranty**

Included accessories: Power cord, instruction manual, remote control connector