

	<b>C.A 6501 IMEG 500N</b>	<b>C.A 6503 IMEG 1000N</b>
<b>Insulation (MΩ calibre)</b>		
Test voltage (DC)	500 V	250 V / 500 V / 1000 V
Range	0.5 to 200 MΩ	1 to 5000 MΩ
Accuracy	2.5 % at full scale	2% at full scale
<b>Resistance</b>		
Range	45 to 500 kΩ	—
Accuracy	2.5% at full scale	—
<b>Continuity</b>		
Range	0 to 100 Ω	—
Accuracy	2% at full scale	—
<b>Voltage</b>		
Range	0 to 600 Vac	0 to 600 Vac
Frequency	45 to 450 Hz	45 to 450 Hz
Accuracy	3% at full scale	3% at full scale
<b>Other Features</b>		
Display	Analog	Analog
Dimensions	120 x 120 x 130 mm	120 x 120 x 130 mm
Weight	1.06 kg	1.06 kg
Power supply	Hand-cranked magneto: stable, constant test voltage	Hand-cranked magneto: stable, constant test voltage
Protection rating	High protection: IP 54 with cover / IP 52 without	High protection: IP 54 with cover / IP 52 without
Electrical safety	IEC 61010 – 600 V CAT II / 300 V CAT III	IEC 61010 – 600 V CAT II / 300 V CAT III

 : No batteries required