

CA MiniFLEX™ MA100 Series		30 A / 300 A	300 A / 3000 A	300 A / 3000 A
Lungime senzor		170 mm	250 mm	350 mm
Diametru cleste		Ø 45 mm	Ø 70 mm	Ø 100 mm
Raport (mV/A)		100 mV/A – 10 mV/A	10 mV/A – 1 mV/A	10 mV/A – 1 mV/A
Domeniu de masura		0.5 A – 30 A 0.5 A – 300 A	0.5 A – 300 A 0.5 A – 3000 A	0.5 A – 300 A 0.5 A – 3000 A
Latime de banda (-3dB)		5 Hz to 20 kHz		
Conector izolat banana Ø 4 mm cu spatiu 19 mm:				
	Cod	P01120560	P01120561	P01120562
BNC + adaptor banana Ø 4 mm:				
	Cod	P01120563	P01120564	P01120565
Tensiune de varf max		4,5 V		
Baterie		9 V		
Siguranta		Izolatie dubla IEC 61010, CAT III 600 V, senzor B 600 V CAT IV / 1000 V CAT III		
Etanseitate		IP65		
Temperatura de operare		-10°C ...+55°C		
Dimensiuni		150 x 64 x 28 mm		
Greutate		250 g ... 560 g.		