

## Technical Data

### Mains Power Supply

- Connection: according to IEC/EN60320-1; UL498, CSA 22.2
- Mains supply: 90 – 264 V AC, 50/60 Hz or 110 – 350 V DC
- Input power: 250 VA
- Fuse: 2 A / 250 V, type F, not user replaceable

### Measurement

- Turns ratio measuring range 0,8 – 15 000
- Turns ratio resolution 5 digits
- Typical turns ratio accuracy:

@125 V AC	@40 V AC
0,8 – 999: $\pm 0,05\%$	0,8 – 999: $\pm 0,05\%$
1 000 – 3 999: $\pm 0,05\%$	1 000 – 3 999: $\pm 0,1\%$
4 000 – 15 000: $\pm 0,1\%$	4 000 – 15 000: $\pm 0,2\%$

@8 V AC	@1 V AC
0,8 – 999: $\pm 0,05\%$	0,8 – 999: $\pm 0,05\%$
1 000 – 3 999: $\pm 0,1\%$	1 000 – 3 999: $\pm 0,1\%$
4 000 – 15 000: $\pm 0,2\%$	
- Excitation current range 0 – 2 A
- Excitation current resolution:

0,0000 – 9,9999 mA	0,1 $\mu$ A
10,000 – 99,999 mA	1 $\mu$ A
100,00 – 999,99 mA	10 $\mu$ A
1,0000 – 2,0000 A	100 $\mu$ A
- Typical excitation current accuracy  $\pm (0,25\% + 500 \mu\text{A})$
- Phase angle range 0 – 360°
- Phase angle resolution 0,01°
- Typical phase angle accuracy  $\pm 0,05^\circ$

### Output Data

- Test voltages  
1 V, 8 V, 40 V, 125 V AC  
3 x (1, 8, 40, 125) $\sqrt{3}$  V AC

### Display

- LCD screen 20 characters by 4 lines;
- LCD display with backlight, visible in bright sunlight

### Interface

- USB (standard)
- RS232 (optional)

### Data Storage

- TRT43A can store up to 10 000 test results

### Environmental Conditions

- Operating temperature:  
-10 °C – +55 °C / 14 °F – +131 °F
- Storage & transportation:  
-40 °C – +70°C / -40 °F – +158 °F
- Humidity: 5 % – 95 % relative humidity, non condensing

### Dimensions and Weight

- Dimensions (W x H x D):  
480 x 190 x 385 mm  
18.90 x 7.48 x 15.16 in
- Weight: 9 kg / 19.8 lbs

### Warranty

- 3 years

### Applicable Standards

- Installation/Overtoltage category: II
- Pollution degree: 2
- Safety: LVD 2006/95/EC (CE Conform)  
Standard EN 61010-1:2001
- EMC: Directive 2004/108/EC (CE Conform)  
Standard EN 61326-1:2006