

Measured Quantity	Measuring Range / Nominal Range of Use	Resolution	Additional Info	Open-Circuit Voltage U_0	Additional Info	Short-Circuit Current I_K	Int. Resist. R_I	Ref. Resist. R_{REF}	Measuring Error	Intrinsic Error	Overload Capacity	
											Value	Time
R_{PE} Protective earth resistance	man: 1 ... 999 mΩ man: 0.01 ... 9.99 Ω	1 mΩ 10 mΩ	Electronic fuse + fuse link	4.0 ... 4.5 V AC TRMS	where $I_{PE} = 200$ mA~ where 48 Hz 1)	220 ... 270 mA AC TRMS	—	—	< ±10% rdg. within a rage of 0.1 ... 10 Ω for IP = 200 mA	±(2.5% rdg. + 10 mΩ) within a rage of 0.1 ... 10 Ω where IP = 200 mA	240 V AC/DC	Cont.
	auto: 0.01 ... 30.00 Ω 0.01 ... 3.30 Ω 0.1 ... 10.0 Ω	10 mΩ 10 mΩ 100 mΩ										
R_{INS} Insulation resistance	10 ... 300 kΩ	10 kΩ	Test voltage: 500 V DC 2)	$U_N < U < 1.2 U_N$	Nominal current > 1 mA where $R_{ISO} = 500$ kΩ	2 mA	—	—	0.01 ... 100 MΩ: < ±10% rdg. > 100 MΩ < ±20% rdg. where UP = 500 V each	0.1 ... 30 MΩ: ±(2.5% rdg. + 1 d) > 30 MΩ ±(5 % rdg. + 1 d) where UP = 500 V each	240 V AC/DC	Cont.
	0.01 ... 3.0 MΩ	10 kΩ										
	0.1 ... 30.0 MΩ	100 kΩ										
	1 ... 300 MΩ	1 MΩ										

Leakage Current Measurements – Direct Method (DIR/DL)

I_E Equipment leakage current	10 ... 300 μA~ 0.01 ... 3.00 mA at 0.1 ... 30.0 mA at	1 μA 10 μA 100 mA	= Protective earth current, direct (between L and N) Residual current monitoring, Mains shutdown: > 20 mA~ (25 ms)						0.5 ... 20.0 mA: < ±10% rdg.	20 ... 300 μA: ±(5% rdg. + 1 d) > 300 μA: ±(2.5% rdg. + 1 d)	240 V AC/DC	Cont.
I_T Touch current	10 ... 300 μA~ 0.01 ... 3.00 mA at 0.1 ... 30.0 mA at	1 μA 10 μA 100 μA	Probe current monitoring: Probe shutdown: $I_T > 10$ mA~ (5 ms) Residual current monitoring Mains shutdown: $I_{DE} > 10$ mA~ (25 ms)				1 kΩ ±10 Ω	—	0.02 ... 10 mA at: < ±10% rdg.	20 ... 300 μA at: ±(5% rdg. + 1 d) > 300 μA at: ±(2.5% rdg. + 1 d)	240 V AC/DC	Cont.
I_P Patient leakage current	2 ... 300 μA~ 0.01 ... 3.00 mA at	1 μA 10 μA	Probe current monitoring: Probe shutdown: $I_P > 10$ mA~ (5 ms) Residual current monitoring Mains shutdown: $I_{DE} > 10$ mA~ (25 ms)				1 kΩ ±10 Ω	—	0.01 ... 3 mA at: < ±10% rdg.	10 ... 300 μA at: ±(7.5% rdg. + 1 d) 0.30 ... 3.00 mA at ±(2.5% rdg. + 1 d)	240 V AC/DC	Cont.
I_{AP} Applied parts leakage current	10 ... 300 μA~ 0.01 ... 3.00 mA~ 0.1 ... 30.0 mA~	1 μA 10 μA 100 mA	Test voltage: 110/220/230/240 V AC	110 ... 240 V~ -15 / +10%	Fre-quency 50/60/200/400 Hz	< 1.5 mA	> 150 kΩ	1 kΩ ±10Ω	20 μA ... 15 mA AC: < ±10% rdg. > 15.0 mA AC: < ±15% rdg.	20 μA ... 15 mA AC: ±(5% rdg. + 1 d) > 15.0 mA AC: ±(10% rdg. + 1 d)	240 V AC/DC	Cont.

Leakage Current Measurements – Differential Method (DIF)

I_E I_T Residual current between L and N	10 ... 300 μA~ 0.01 ... 3.00 mA~ 0.1 ... 30.0 mA	1 μA 10 μA 100 μA	= Protective earth current, direct Residual current monitoring Mains shutdown: > 20 mA~ (25 ms)						0.5 ... 20.0 mA: < ±10% rdg.	20 ... 300 μA: ±(5% rdg. + 1 d) > 300 μA: ±(2.5% rdg. + 1 d)	240 V AC/DC	Cont.
--	--	-------------------------	---	--	--	--	--	--	---------------------------------	---	-------------	-------

Leakage Current Measurements – Alternative Method: Alternative leakage current (ALT)

I_E I_T I_{AP}	2 ... 300 μA~ 0.01 ... 3.00 mA~ 0.1 ... 30.0 mA~	1 μA 10 μA 100 μA	Test voltage: 110/220/230/240 V AC	110 ... 240 V~ V~ -15 / +10%	Fre-quency 50/60 Hz 3)	< 1.5 mA	> 150 kΩ	1 kΩ ±10Ω	20 μA ... 15 mA AC: < ±10% rdg. > 15.0 mA AC: < ±15% rdg.	20 μA ... 15 mA AC: ±(5% rdg. + 1 d) > 15.0 mA AC: ±(10% rdg. + 1 d)	240 V AC/DC	Cont.
---	--	-------------------------	------------------------------------	---------------------------------------	------------------------	----------	----------	--------------	--	---	-------------	-------

Function test

U_{LN} Line voltage (RMS)	90 ... 240 V AC (50 ... 400 Hz)	0.1 V							±5.0% rdg.	±(2.5% rdg. + 1 d)	240 V AC	Cont.
I_V Load current (RMS)	0.02 ... 16.00 A AC (50 ... 400 Hz)	10 mA	Shutdown by mains relay at: $I_V > 16$ A~ where $t > 0.5$ s Shutdown by mains relay at: $I_V > 4$ A~ where internal temperature > 70 °C						±5.0% rdg.	±(2.5% rdg. + 1 d)	4 A	Cont.
P Active power	10 ... 4000 W	1 W	Measured value P and calculated value S are compared, and the smaller of the two is displayed.						f < 100 Hz ±7.5% rdg.	P > 10 W, PF > 0.5 f < 100 Hz ±(5% rdg. + 10 d)	< 1000 W	Cont.
			Shutdown at internal temperature > 70 °C						f ≥ 100 Hz ±10% rdg.	P > 10 W, PF > 0.5 f ≥ 100 Hz ±(7.5% rdg. + 10 d)	< 4000 W	10 min
S Apparent power	10 ... 4000 W	1 VA	Calculated vale $U_{L-N} \cdot I_V$						f < 100 Hz ±7.5% M	P > 10 W f < 100 Hz ±(5% rdg. + 10 d)	< 1000W	Cont.
			Shutdown at internal temperature > 70 °C						f ≥ 100 Hz ±10% rdg.	P > 10 W f ≥ 100 Hz ±(7.5% rdg. + 10 d)	< 4000W	10 min
LF Power factor with sinusoidal waveshape: cos φ	0.00 ... 1.00 inductive	0.01	Calculated value P / S, display as of P > 10 W						f < 100 Hz ±7.5% M	P > 10 W, PF > 0.5 f < 100 Hz ±(5% rdg. + 10 d)	—	—
									f ≥ 100 Hz ±10% rdg.	P > 10 W, PF > 0.5 f ≥ 100 Hz ±(7.5% rdg. + 10 d)		