

Function	Range	Accuracy
DC voltage	400.0 mV	±(0.3 % of reading + 4 digits)
	4.000V, 40.00V, 400.0V	±(0.5 % of reading + 3 digits)
	600V	±(1.0 % of reading + 4 digits)
AC voltage, 50 Hz - 500 Hz	4.000V, 40.00V, 400.0V	±(1.5 % of reading + 5 digits)
	600V	±(2.0 % of reading + 5 digits)
AC current measurement, 50,60 Hz	40.00A, 400.0A, 600A	±(1.5 % of reading + 8 digits)
Resistance measurement	400.0 Ω	±(0.8 % of reading + 6 digits)
	4.000 kΩ, 40.00 kΩ, 400.0 kΩ	±(0.6 % of reading + 4 digits)
	4.000 MΩ	±(1.0 % of reading + 4 digits)
	40.00 MΩ	±(2.0 % of reading + 4 digits)
Diode test	Open-circuit voltage <1.6 V DC, test current 0.25 mA	
Frequency	10 Hz ÷ 400 Hz	±(0.5 % of reading + 4 digits)
Capacitance	500 nF ÷ 3000 μF	±(3.5 % of reading + 6 digits)
Power supply	3 V battery, IEC-CR2032	
Overvoltage category	CAT III/600 V	
Pollution degree	II	