

Function	Range	Resolution	Accuracy	Test current
Resistance	1,9999 mΩ	0,1 µΩ	±(0,25% Rdg + 0,01% FS)	10 A
	19,999 mΩ	1 µΩ	±(0,25% Rdg + 0,01% FS)	10 A/1 A
	199,99 mΩ	10 µΩ	±(0,25% Rdg + 0,01% FS)	10 A/1 A/100 mA
	1,9999 Ω	100 µΩ	±(0,25% Rdg + 0,01% FS)	1 A/100 mA/10 mA
	19,999 Ω	1 mΩ	±(0,25% Rdg + 0,01% FS)	100 mA/10 mA
	19,999 Ω	10 mΩ	±(1% Rdg + 0,1% FS)	1 mA
	199,99 Ω	10 mΩ	±(0,25% Rdg + 0,01% FS)	10 mA
	199,99 Ω	100 mΩ	±(1% Rdg + 0,25% FS)	1 mA
	1,9999 kΩ	1 Ω	±(1% Rdg + 0,25% FS)	1 mA
Power supply (mains voltage)	90 ... 260 VAC / 60 VA			
Power supply (batteries)	6 x 1,2 V NiMH 3500 mAh batteries, type C			
Operation	> 1000 single measurements			
Oversupply category	CAT IV / 300 V			
Protection class	Double insulation			
Display	320 x 240 LCD with backlight			
Communication	RS232 and USB			
Memory	1000 memory locations			
Dimensions	310 x 130 x 250 mm			
Weight	2.8 kg			