

MX 407

Voltage measurement		
	Range	0 to 600 V _{AC/DC} ±0.8 % ±3 cts (DC)
	Accuracy	±1.2 % ±10 cts (AC)
Insulation		
Voltage testing	250 V	10 kΩ to 4 GΩ
	500 V	10 kΩ to 4 GΩ
	1,000 V	10 kΩ to 4 GΩ
Accuracy	Range 4 MΩ / 40 MΩ	±2 % ±10 cts
	Range 400 MΩ	±2 % ±5 cts
	Range 4 GΩ	±4 % ±5 cts
Voltage alert indicator		Yes > 25 V
Test inhibition		Yes > 25 V
Continuity		
Range		0.0 to 400 Ω
Measurement current		≥ 200 mA
Cable compensation		Yes
Audio signal		Audio signal triggered at < 35 Ω ±3 Ω
Résistance		
Range		0.00 to 400 kΩ
Accuracy		±1.2 % ± 3 cts
Automatic shutdown		After 10 minutes without use
Display		LCD + Bargraph
Backlighting		Yes
Power supply		6 x 1.5 V AA batteries
Dimensions		H 200 x W 92 x D 50 mm
Weight		700 g (with batteries)
Electrical safety		IEC 61010 600 V CAT IV / IEC 61557-3-4