




	MX 24	MX 24B	MX 26
			
Masuratori	TRMS CA + CC		TRMS CA & CA + CC
Latime de banda	1 kHz		100 kHz
Tensiune CC	500.0 mV la 1,000 V		
Precizie CC	0.3 % R + 2 D		
Tensiune AC sau AC + CC	500.0 mV la 750 V		
Precizie tensiune AC sau AC + CC	1.5 % R + 2 D		1 % R + 3 D
Curent CC / AC + CC	50.00 mA - 20.00 A	500.0 mA - 20.00 A	500.0 mA - 10.00 A
Precizie CC	0.3 % R + 2 D		
Precizie curent AC sau AC + CC	1.5 % R + 2 D		
Rezistenta	5,0000 Hz la 500,00 kHz		
Precizie	0,03% + 2D		
Test continuitate (buzzer)	< 10-20 Ω / 10ms		<10-15 Ω / 1ms
Test dioda	●		
Frecventa	5,0000 Hz la 500,00 kHz		
Precizie	0,03% + 2D		
Capacitanta	De 50,00 nF la 50,00 mF		
Precizie	1% L + 4D		
Filtru motor viteza variabila	Latime de banda 1 kHz		—
V <sub>LowZ</sub>	5.000 V la 750 V (AC+DC)		5.000 V la 750 V (AC)