

TECHNICAL SPECIFICATIONS		AX 1360-P
Number of outputs	3	
VOLTAGE CONTROL		
Output 1	0 – 30 V	
Output 2	0 – 30 V	
Output 3	2.5 V / 3.3 V / 5 V	
CURRENT CONTROL		
	INDEPENDENT	PARALLEL
Output 1	5 A	6 A
Output 2	5 A	10 A
Output 3	3 A	-
ACCURACY		
Voltage	±(0.5 % reading + 2 digits)	
Current	±(0.5 % reading + 5 digits)	
RESOLUTION		
Voltage	10 mV (0 to 9.99 V) – 100 mV (10 to 30 V)	
Current	10 mA	
RIPPLE AND NOISE		
Voltage	< 1 mV RMS	
TEMPERATURE COEFFICIENT		
Voltage	< 300 ppm/°C	
ON-LOAD		INDEPENDENT AND PARALLEL
Voltage control	< 0.1 % + 5 mV	
Current control	< 0.2 % + 3 mA	
PROTECTION		
Short-circuits	Current limitation and visual indicated by red LED	
Overcurrent	Fuse	
“SAVE/RECALL” FUNCTION		
No. of stored configurations	4	
TECHNICAL SPECIFICATIONS		
Display	Digital with LEDs – Simultaneous voltage and current in colour	
Current and voltage adjustment	Output 1 and 2 by potentiometers, Output 3 by switch	
Interface / Software	USB / Drivers LV and LW	
Mains power source	220 V / 50 Hz – 60 Hz	
Safety / Protection	IEC 61010-1 / Fuse	
Mechanical specifications	Dimensions: 310 x 250 x 150 mm – Weight: 7.5 kg	
Warranty	1 year	