

		DMM 111	DMM 121	DMM 141
Display		2.000 puncte	4.000 puncte	
Mod de masurare		Medie		RMS
I _{DC}	Domenii	200 µA / 2000 µA / 20 mA / 200 mA / 2 A / 10 A (20A max / 30 s max)	400 µA / 4000 µA / 40 mA / 400 mA / 4 A / 10 A (20A max / 30 s max)	
	Precizie	1%R + 3 cts		
	Rezolutie	0,1 µA		
I _{AC}	Domenii	200 µA / 2000 µA / 20 mA / 200 mA / 2 A / 10 A (20A max / 30 s max)	400 µA / 4000 µA / 40 mA / 400 mA / 4 A / 10 A (20A max / 30 s max)	
	Precizie	1%R + 5 cts		
	Rezolutie	0,1 µA		
V _{DC}	Domenii	200 mV / 2 V / 20 V / 200 V / 600 V	400 mV / 4 V / 40 V / 400 V / 600 V	400 mV / 4 V / 40 V / 400 V / 600 V
	Precizie	0.5%R + 3 cts		
	Rezolutie	0,1 mV		
V _{AC}	Domenii	200 mV / 2 V / 20 V / 200 V / 600 V	400 mV / 4 V / 40 V / 400 V / 600 V	
	Precizie	1%R + 5 cts		
	Rezolutie	0,1 mV		
Rezistenta	Domenii	200 Ω / 2 kΩ / 20 kΩ / 200 kΩ / 2 MΩ / 20 MΩ	400 Ω / 4 kΩ / 40 kΩ / 400 kΩ / 4 MΩ / 40 MΩ	
	Precizie	0.5%R + 2 cts		
	Rezolutie	0.1 Ω		
Continuitate (buzzer)		Da		
Test dioda		Da		
Frecventa			5 Hz / 50 Hz / 500 Hz / 5 kHz / 50 kHz / 500 kHz / 50 MHz	
Capacitanta			50 nF / 500 nF / 5 µF / 50 µF / 100 µF	
Scalare		Automat/Manual		
Alte caracteristici		Data hold, power-off dezactivabil, MAX	Iluminare, data hold, power-off dezactivabil, mod relativ	
Siguranta		600 V CAT III IEC 61010-1, 61010-2-033		
Dimensiuni/greutate		181 x 92 x 57 mm / 335 g (fara baterii)		